

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Grant		C 1/4 N 1/4 SW 1/4		25		T 30 S		R 35 E	
Distance and direction from nearest town or city street address of well if located within city?									
From Satanta: 2SW to Miller Feed Lot sign, 5W, 2S & E into--									
2 WATER WELL OWNER:		OXY USA, Inc.				#1 MLP Watson A 980333			
RR#, St. Address, Box # :		P. O. Box 26100				Board of Agriculture, Division of Water Resources			
City, State, ZIP Code :		Oklahoma City, OK 73126				Application Number: OXY permitted			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 320 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. 135 ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 135 ft. below land surface measured on mo/day/yr 09/28/92							
		Pump test data: Well water was 145 ft. after 1 hours pumping 100 gpm							
		Est. Yield 100 gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 9 1/2 in. to 320 ft., and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes X No							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		Welded							
2 PVC 4 ABS		Threaded							
Blank casing diameter 5 in. to 320 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. 280 SDR-21									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 200 ft. to 320 ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 180 ft. to 320 ft., From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole Plug									
Grout intervals: From 1 ft. to 20 ft., From ft. to ft., From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? Northeast		How many feet? 250							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 3 Sand									
3 15 Sand & Gravel									
15 130 Gravel									
130 140 Tan Clay									
140 225 Sand & Gravel									
225 273 Sandy Clay									
273 285 Sand									
285 320 Clay & Sandy Clay									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/28/92 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430 This Water Well Record was completed on (mo/day/yr) 9/28/92 under the business name of Howard Drlg. Co. Box 806 Beaver, OK 73932 by (signature)									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send up three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									