

1 LOCATION OF WATER WELL:	Fraction	Section Number	Township Number	Range Number
County: Grant	SE ¼ SE ¼ NW ¼	26	T 30 S	R 35 EW

Distance and direction from nearest town or city street address of well if located within city?

From Rynis, KS, 5½ miles South

2 WATER WELL OWNER:	OXY USA, Inc.	#1 MLPSCott A
RR#, St. Address, Box # :	P. O. Box 26100	Board of Agriculture, Division of Water Resources
City, State, ZIP Code :	Oklahoma City, OK 73126-0100	Application Number: OXY permitted

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL: 380 ft. ELEVATION:
	Depth(s) Groundwater Encountered 1. 175 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 175 ft. below land surface measured on mo/day/yr 11/06/91 Pump test data: Well water was 200 ft. after 1 hours pumping 100 gpm Est. Yield 100 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 9½ in. to 380 ft., and in. to ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 8 Air conditioning 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 9 Dewatering 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED:	5 Wrought iron	8 Concrete tile	CASING JOINTS: Glued X Clamped
1 Steel	3 RMP (SR)	6 Asbestos-Cement	9 Other (specify below)
2 PVC	4 ABS	7 Fiberglass	Welded
Blank casing diameter 5 in. to 380 ft., Dia			Threaded
Casing height above land surface 24 in., weight			lbs./ft. Wall thickness or gauge No. .032
TYPE OF SCREEN OR PERFORATION MATERIAL:	7 PVC	10 Asbestos-cement	
1 Steel	3 Stainless steel	5 Fiberglass	8 RMP (SR)
2 Brass	4 Galvanized steel	6 Concrete tile	9 ABS
SCREEN OR PERFORATION OPENINGS ARE:	5 Gauzed wrapped	8 Saw cut	11 None (open hole)
1 Continuous slot	3 Mill slot	6 Wire wrapped	9 Drilled holes
2 Louvered shutter	4 Key punched	7 Torch cut	10 Other (specify)
SCREEN-PERFORATED INTERVALS:	From 300 ft. to 380 ft., From		
	From ft. to ft., From		
GRAVEL PACK INTERVALS:	From 260 ft. to 380 ft., From		
	From ft. to ft., From		

6 GROUT MATERIAL:	1 Neat cement	2 Cement grout	3 Bentonite	4 Other Hole Plug
Grout intervals:	From 1 ft. to 20 ft., From			
What is the nearest source of possible contamination:				
1 Septic tank	4 Lateral lines	7 Pit privy	10 Livestock pens	14 Abandoned water well
2 Sewer lines	5 Cess pool	8 Sewage lagoon	11 Fuel storage	15 Oil well/Gas well
3 Watertight sewer lines	6 Seepage pit	9 Feedyard	12 Fertilizer storage	16 Other (specify below)
			13 Insecticide storage	

Direction from well?	Southeast	How many feet?	150		
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	Top Soil	262	307	Clay
4	77	Sand and Gravel	307	316	Fine Sand
77	85	Clay	316	326	Sandy Clay
85	94	Sand	326	372	Sand and Gravel
94	102	Clay	372	380	Clay
102	109	Sand and Gravel			
109	116	Sandy Clay			
116	138	Sand			
138	146	Sandy Clay			
146	172	Gravel and Sand w/Clay Streaks			
172	204	Sand and Gravel			
204	216	Gravel and Clay			
216	225	Sand			
225	234	Sandy Clay			
234	262	Sand and Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION:	This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 11/05/91 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL - 430 This Water Well Record was completed on (mo/day/yr) 11/05/91 under the business name of Howard Drilling Co. Box 806 Beaver, OK by (signature)
--	---

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.