WATEI	R WELL	RECORD]	Form W	WC-5	Division of V	Vater Resources; App. No.		
l		F WATER WELL:		ction	1/2	Section Number	1 1		
	ty: Gran	nt ection from nearest tow			1/4 NW 1/4	Clabal Basitian	T 30S	R 35W ENW	
	nce and dir ed within ci					T 1	ing Systems (decimal deg	, ,	
iocan	ou within Ci	ty: Kyus: 1 w-	-s s and	е шис) 				
2 WATER WELL OWNER: SW Windmill Jose Cano						Elevation:			
1	, St. Addres	D. "	Box 909		ose cano	Datum:			
	State, ZIP	2 1	, KS 67			Data Collecti	on Method:		
3 100	ATE WEI			Data Concert					
ı	ATION	LS 4 DEI III OF	COMILEI	ED WEI	2.1.		. 16.		
SEC'	CTION BOX: WELL'S STATIC WATER LEVEL29.2ft. below land surface measured on mo/day/yr08-24-09								
	N	Pump te	st data: W	ell water v	was	ft. after	hours pumping.	gpm	
X							hours pumping.		
	WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)								
W E 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well									
'			T Industria	n / D	oniestie (iawi	ice garden) 10 1	wiomtoring wen		
SV	SW SE Was a chemical/bacteriological sample submitted to Department? Yes NoX; If yes, mo/day/yrs								
							ed? YesX No		
S									
5 TYPI	E OF CAS	ING USED: 5 Wi	ought Iron		8 Concrete til	e CAS	SING JOINTS: Glued	Clamped	
1	Steel		bestos-Cem	ent 9	Other (speci	fy below)	Welded.		
		4 ABS 7 Fib	erglass				Threade	d	
Blank casing diameter 5 in. to 30.0 ft., Diameter in. to ft., Diameter in. to ft., Diameter in. to 5 in. to 5 ft. Casing height above land surface 24 in., Weight 3.706 lbs./ft. Wall thickness or guage No. SDR 21316									
					3,./00	lbs./ft. Wall	thickness or guage No.	DDK .41•310	
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless Steel 5 Fiberglass 7 VC 9 ABS 11 Other (Specify)									
1 Steel 3 Stainless Steel 5 Fiberglass 7 VC 9 ABS 11 Other (Specify)									
SCREEN OR PERFORATION OPENINGS ARE:									
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 7 Torch cut 9 Drilled holes 11 None (open hole)									
2 Louvered shutter 4 Key punched 6 Wire wrapped 8 aw cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From									
From									
GRAVEL PACK INTERVALS: From									
rioni									
		ERIAL: Uneat ceme	nt 2 Ceme	ent grout	3 Bentonite	4)Other	Hole Plug		
Grout Ir				ft., Fr	om	ft. to	ft., From	ft. toft.	
1		source of possible cont			10 1	ato als mana 11	2 Importisido atomoro	16 Other (amonify	
1	Septic tank Sewer line		lines 7 Pit	privy wage lago			Insecticide storageAbandoned water well	16 Other (specify below)	
1		sewer lines 6 Seepag					5 Oil well/gas well		
		1?							
FROM	TO		LOGIC LO		FRC		PLUGGING IN		
0	3	Surface							
3	40	Sandy Clay and	Clay						
40	44	Sand							
44	66	Clay					·		
66	83	Clay and Gravel							
83_	153	Sand and Gravel							
153	223	Clay							
223	346						THE STATE OF THE S		
346	360	Sandy Clay							
360 380 Sand 7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was Doonstructed, (2) reconstructed, or (3) plugged									
under my jurisdiction and was completed on (mo/day/year) 08-24-09 and this record is true to the best of my knowledge and belief.									
Kansas Water Well Contractor's License NoKWWCL-430. This Water Well Record was completed and two/day/year) 08-24-09									
under the business name of Howard Drlg. Co. Sox 806 Beaver, QK (Application)									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline of circle the correct answers. Send top									
three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each constructed well. Visit us at									
http://www.kdheks.gov/waterwell/index.html.									