

1 LOCATION OF WATER WELL: Fraction NE 1/4 SE 1/4 SE 1/4 Section Number 16 Township Number T 30 S Range Number R 36 EW

Distance and direction from nearest town or city street address of well if located within city? From Hickok 1 mile East 9 mile So. 2 mile West 1/2 No. 80' West

2 WATER WELL OWNER: Kantex Feeders RR#, St. Address, Box #: Box 1105 City, State, ZIP Code: Ulysses, Ks. 67880 Board of Agriculture, Division of Water Resources Application Number: 30648

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of a 2x2 grid with NW, NE, SW, SE quadrants. The SE quadrant contains an 'X'. A vertical line labeled 'N' is on the left, and a horizontal line labeled 'S' is at the bottom. A vertical line labeled 'W' is on the left, and a horizontal line labeled 'E' is on the right. A vertical scale bar on the far left is labeled '1 Mile'.] 4 DEPTH OF COMPLETED WELL: 320 ft. ELEVATION: ... WELL'S STATIC WATER LEVEL: 160 ft. below land surface measured on mo/day/yr 6-17-84. Pump test data: Well water was ... ft. after ... hours pumping ... gpm. Est. Yield ... gpm: Well water was ... ft. after ... hours pumping ... gpm. Bore Hole Diameter: 15 in. to 320 ft., and ... in. to ... ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes ... No [X] ...; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes [X] No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ... Clamped ... 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded [X] Threaded ... Blank casing diameter 8 5/8 in. to 320 ft., Dia ... in. to ... ft., Dia ... in. to ... ft. Casing height above land surface: 12 in., weight 16.9 lbs./ft. Wall thickness or gauge No. .188 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut SCREEN-PERFORATED INTERVALS: From 240 ft. to 320 ft. From ... ft. to ... ft. GRAVEL PACK INTERVALS: From 220 ft. to 320 ft. From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From 0 ft. to 10 ft., From ... ft. to ... ft., From ... ft. to ... ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet? 150

Table with 6 columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, LITHOLOGIC LOG. The content is mostly empty, with the text 'Test log attached' centered in the middle of the first three columns.

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 8-24-84 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 9-12-84 under the business name of Minter Wilson Drilling Co. by (signature) K. H. Saraman

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY

T

30

R

36

EW

SEC.

16

NE 1/4

SE 1/4

SW 1/4

EW

Handwritten initials 'DP' at the bottom right corner.