


1 LOCATION OF WATER WELL: County: Grant Fraction: SE 1/4 SE 1/4 NW 1/4 Section Number: 23 Township Number: T 30 S Range Number: R 36 EW

Distance and direction from nearest town or city street address of well if located within city?
10 miles south and 7 1/2 miles east of Ulysses, Kansas

2 WATER WELL OWNER: Melvin Teeter
RR#, St. Address, Box #: 310 S. Maxwell Board of Agriculture, Division of Water Resources
City, State, ZIP Code: Ulysses, Kansas 67880 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 300 ft. ELEVATION: slope
Depth(s) Groundwater Encountered: 1. 160 ft. 2. ft. 3. ft.
WELL'S STATIC WATER LEVEL: 160 ft. below land surface measured on mo/day/yr 9/22/88.
Pump test data: Well water was ft. after hours pumping gpm
Est. Yield gpm: Well water was ft. after hours pumping gpm
Bore Hole Diameter: 9 3/4 in. to 300 ft., and in. to ft.
WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well windmill well
Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted
Water Well Disinfected? Yes X No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded X
2 PVC 4 ABS 7 Fiberglass and riveted Threaded
Blank casing diameter: 5 in. to 260 ft., Dia. in. to ft., Dia. in. to ft.
Casing height above land surface: 24 in., weight lbs./ft. Wall thickness or gauge No. schedule 80
TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
SCREEN-PERFORATED INTERVALS: From 260 ft. to 300 ft., From ft. to ft.
GRAVEL PACK INTERVALS: From 20 ft. to 300 ft., From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
Grout Intervals: From 0 ft. to 20 ft., From ft. to ft., From ft. to ft.
What is the nearest source of possible contamination:
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage drilled in pasture
Direction from well? How many feet?

| FROM | TO | LITHOLOGIC LOG | FROM | TO | PLUGGING INTERVALS |
|------|-----|-------------------------------------|------|----|--------------------|
| 0 | 2 | Surface | | | |
| 2 | 35 | Clay w/some fine sand | | | |
| 35 | 48 | Clay | | | |
| 48 | 54 | Coarse sand | | | |
| 54 | 139 | Brown clay | | | |
| 139 | 180 | Fine to medium sand w/clay breakers | | | |
| 180 | 197 | Medium sand | | | |
| 197 | 220 | Gray clay w/lime shells | | | |
| 220 | 272 | Fine to medium sand w/clay breakers | | | |
| 272 | 297 | Coarse sand | | | |
| 297 | 315 | Yellow chalk w/hard sandstone | | | |

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 9/22/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 164 This Water Well Record was completed on (mo/day/yr) 5/23/89 under the business name of Houck Bros. Drilling co. by (signature) M. Beard