


1 LOCATION OF WATER WELL: County: Grant		Fraction SE 1/4 SE 1/4 SW 1/4	Section Number 9	Township Number T 30 S	Range Number R 37 E/W
Distance and direction from nearest town or city street address of well if located within city? 9 miles south and 1/2 west of Ulysses, Kansas					
2 WATER WELL OWNER: RR#, St. Address, Box # : City, State, ZIP Code		Seaboard Farms, Inc. P. O. Box 1029 Hugoton, Kansas 67951			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 396 ft. ELEVATION: slope			
		Depth(s) Groundwater Encountered 1. 230 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 230 ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was Pump not installed by us hours pumping gpm Bore Hole Diameter: 15 in. to 396 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well stock Was a chemical/bacteriological sample submitted to Department? Yes No X If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 2 PVC 4 ABS		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued X Clamped 6 Asbestos-Cement 9 Other (specify below) & riveted Welded 7 Fiberglass Threaded			
Blank casing diameter 8 in. to 29.6 ft. Dia 8 in. to 3.56 ft. Dia in. to ft. Casing height above land surface 18 in. weight schedule 200 SDR 11.5 ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS		7 PVC 10 Asbestos-cement 11 Other (specify) 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes		7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From 296 ft. to 336 ft. From 356 ft. to 396 ft. From 24 ft. to 396 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 24 ft. to 396 ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) none					
Direction from well?		How many feet?			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	2	Surface			
2	60	Fine sand w/clay breakder			
60	95	Fine to medium sand w/clay breakers			
95	145	Brown clay			
145	230	Fine sand			
230	290	Medium sand			
290	342	Medium to coarse sand			
342	363	Sandy clay			
363	386	Fine to medium sand			
386	396	Fine sand w/clay breakers			
396	420	Yellow chalk & hard sandstone			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 7/19/95 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 164 This Water Well Record was completed on (mo/day/yr) 7/21/95 under the business name of Houck Bros. Drilling Co. by (signature) M. Beard					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					

OFFICE USE ONLY

T

R

E/W

SEC.

1/4

1/4

1/4

000493