WATER WELL RECORD Form WWC-5						vision of Wate	r Resources App. N	0.		
1 LOCATION OF WATER WELL:		Fraction		Section	on Number	Township No.	Range Number			
			NW 1/4 NW 1/4	1/4 1/4		10	T 30 S	R 37 □E 🗹 W		
	Street/Rural Address of Well Location; if unknown, distance & direction from nearest town or intersection: If at owner's address, check here .						Global Positioning System (GPS) information:  Latitude: .N37,458722			
	215 East Road 20					Longitude: W101.358307 (in decimal degrees)				
Ulysses, Kansas					Eleva	Elevation:				
						Datum: WGS 84, NAD 83, NAD 27				
RR#, Street Address, Box #: P.O. Box 2788					Collec	Collection Method:  ☐ GPS unit (Make/Model: Handy GPS)				
City, State, ZIP Code : Amarillo, Texas 79105						☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
Est. Accuracy:										
	3 LOCATE WELL WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 110 ft. 5VE-2									
	TION BO	Depth(s) Groundwater Encountered (1)								
	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr									
	Pump test data: Well water wasft. after hours pumping									
WNW NE E EST. YIELD										
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well										
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)										
Irrigation   Industrial   Domestic-lawn & garden   Monitoring well SOII VADOT EXT.										
Was a chemical/bacteriological sample submitted to Department? ☐ Yes ☑ No  If yes, mo/day/yr sample was submitted										
Water well disinfected?  \[ \sqrt{Yes} \sqrt{No} \]										
5 TYPE OF CASING USED: Steel PVC Other										
CASING JOINTS: ☐ Glued ☐ Clamped ☐ Welded 🗸 Threaded										
Casing diameter .2 in. to .25 ft., Diameter .2 in. to .70 ft., Diameter in. to ft.										
Casing height above land surface12										
TYPE OF SCREEN OR PERFORATION MATERIAL:  Steel Stainless Steel PVC Specify)										
☐ Steel ☐ Stainless Steel ☐ PVC ☐ Other (Specify)										
SCREEN OR PERFORATION OPENINGS ARE:										
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)										
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)  SCREEN-PERFORATED INTERVALS: From										
From										
GRAVEL PACK INTERVALS: From24										
From										
6 GROUT MATERIAL: Neat cement Cement grout Denotite Other										
		est source of possible conta	mination:		11. 10	1b.,	F10III	11. 10		
Septic tank										
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well										
		n well				∷⊡∙Oil well/ga ell	as well			
FROM	ТО	LITHOLOG		FROM	TO			JGGING INTERVALS		
0	2	Brown Silt		62	81	Gray Silt				
2	14	Brown Clay		81	87	Reddish Y				
14	21	Brown Clayey Silt		87	93	Red Silty (		NAME:		
21	30 35	Gray Silt Brown Silt		93	94	Pink Silt- S	Stone			
30 35	42	Gray Silt		94 100	100	Pink Clay	ellow Clav			
42	48	Gray Clay		103	109	Yellowish		AND		
48	50.5	Brown Clay		109	112		ellow Clav			
50.5	61	Pink Silt								
61	62	Pink Clay								
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, □ reconstructed, or □ plugged										
under my jurisdiction and was completed on (mo/day/year) .02/1.5/20.12 and this record is true to the best of my knowledge and belief.  Kansas Water Well Contractor's License No763 This Water Well Record was completed on (mo/day/year) .08/08/2012										
under the business name of Peterson Drilling and Testing, Inc. by (signature)										
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies										
(white, blue, pink) to Kansas Depar tment of Health and E nvironment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Vi sit us at										
http://www.kdheks.gov/waterwell/index.html.										
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy										