


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Grant	Fraction SE 1/4 SE 1/4 NE 1/4	Section number 2	Township number T 30 S R 38 E W	Range number
2. Distance and direction from nearest town or city: 7 S. of Ulysses on Hiway 25, 4 1/8 west, 1/2 south. Street address of well location if in city:			3. Owner of well: Ralph Kepley R.R. or street: Route 2 City, state, zip code: Ulysses, Kansas 67880			
4. Locate with "X" in section below:		Sketch map:		6. Bore hole dia. 26 in. Completion date 2-28-77 Well depth 530 ft.		
				7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary		
5. Type and color of material		From	To	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other		
				9. Casing: Material steel Height: Above surface Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 12 in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 531 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. 250		
				10. Screen: Manufacturer's name Johnson Type galv. Dia. 16" Slot/gage 1/8" Length 20 ft. Set between 300-340 ft. and 460-500 ft. Perf: 340-460 ft. and 500-530 ft. Gravel pack? yes Size range of material 3/4" down		
				11. Static water level: <input type="checkbox"/> mo./day/yr. 170 ft. below land surface Date 2-16-77		
				12. Pumping level below land surfaces: 330 ft. after 3 hrs. pumping 500 g.p.m. 420 ft. after 4 hrs. pumping 300 g.p.m. Estimated maximum yield 300 g.p.m.		
				13. Water sample submitted: <input type="checkbox"/> mo./day/yr. <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date		
				14. Well head completion: <input type="checkbox"/> Pitless adapter 12 inches above grade		
				15. Well grouted? yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.		
				16. Nearest source of possible contamination: N/A ft. <input type="checkbox"/> Direction <input type="checkbox"/> Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No		
				17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Did NOT INSTALL Model number HP Length of drop pipe 1 ft. capacity <input type="checkbox"/> g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other		
18. Elevation:		19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Winter-Wilson Drilling Co. 208 Business name License No. Address Box A Garden City, Ks. Signed [Signature] Date 3-30-77 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

TEST HOLE LOG

Wagner's

Box 10, Ulysses, Kansas 67880

Water Wells & Test Holes

Phone (316) 356-2396

Test No. 5Date 12-1-77Qtr. NE Sec. 2Twp. 30 Rge. 36Co. GrantLand Owner Ralph KopleyAddress Ulysses, Kansas

CONSOLIDATED-SALINA

FOOTAGE	Description of Strata
0 - 20	Surface and brown clay
20 - 120	Brown clay
120 - 140	Sand
140 - 220	Brown clay
220 - 260	Fine sand
260 - 280	Sand & br. clay strips
280 - 300	" " " " " "
300 - 360	Medium to coarse sand: Brown sand clay
360 - 400	Brown clay
400 - 420	" " & sand strips
420 - 460	" " : Cheyenne
460 - 540	Brown shale, white & brown sandstone & Cheyenne: Br. shale
	Hole at 540 ft.

0 - 300 Plain
 300 - 340 Screen
 340 - 460 Perf
 460 - 500 Screen
 500 - 530 Perf
 Drill hole 530 ft.

75%

60%

355-360

10

530-540