


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Grant		NW 1/4 SE 1/4 SE 1/4	2	T 30 S	R 38W EW
Distance and direction from nearest town or city street address of well if located within city? Ulysses, Kansas - 7 3/4 miles South - 4 1/4 miles West in to location.					
2 WATER WELL OWNER: Bernice Kepley		ARCO Exeter 13 Board of Agriculture, Division of Water Resources Application Number: T 88-345			
RR#, St. Address, Box #: Western Prairie		City, State, ZIP Code: Ulysses, Kansas			
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 380' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 155' ft. below land surface measured on mo/day/yr 07/14/88 Pump test data: Well water was 215' ft. after 2 hours pumping 110 gpm Est. Yield 110 gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter 11" in. to 380' ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped Welded Threaded			
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below)		2 PVC 4 ABS 7 Fiberglass			
Blank casing diameter 6.625 in. to ft. Dia in. to ft. Dia in. to ft.		Casing height above land surface -60" in. weight 3.71 lbs./ft. Wall thickness or gauge No. 280			
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)		2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)			
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes		2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)			
SCREEN-PERFORATED INTERVALS: From ft. to ft. From ft. to ft. From ft. to ft.		GRAVEL PACK INTERVALS: From 27' ft. to 130' ft. From 140' ft. to 380' ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other		Grout Intervals: From 5' ft. to 27' ft. From 130' ft. to 140' ft. From ft. to ft.			
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well		2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage		Direction from well? Northeast How many feet? 150'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	dirt .98	cu.	feet of	dirt
5	27	bentonite grout 4.32	cu.	feet of	bentonite grout
27	130	chlorinated gravel 20.22	cu.	feet of	chlorinated gravel
130	140	bentonite grout 1.96	cu.	feet of	bentonite grout
140	380	chlorinated gravel 47.11	cu.	feet of	chlorinated gravel
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 12/14/88 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 118 This Water Well Record was completed on (mo/day/yr) 12/14/88 under the business name of Carlisle Water Well Service, Inc. by (signature)					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks. underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.					