

1 LOCATION OF WATER WELL: Fraction NC 1/4 C/W 1/2 1/4 W 1/2 1/4 Section Number 8 Township Number T 30 S Range Number R 38 **EW**

Distance and direction from nearest town or city street address of well if located within city? FROM ULYSSES 5 WEST 9 SOUTH 2 1/2 WEST, NORTH INTO LOC. "Cruz"

2 WATER WELL OWNER: FRIESEN WINDMILL & SUPPLY RR#, St. Address, Box # : BOX M Board of Agriculture, Division of Water Resources City, State, ZIP Code : MEADE, KS 67864-0470 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX. 4 DEPTH OF COMPLETED WELL: 150 ft. ELEVATION: 150 ft. Depth(s) Groundwater Encountered 1. 110 ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 90 ft. below land surface measured on mo/day/yr 4-7-94 Pump test data: Well water was 110 ft. after 1 hours pumping 3 gpm Est. Yield 3 gpm Well water was ft. after hours pumping gpm Bore Hole Diameter 9 1/2 in. to 150 ft., and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 7 Fiberglass 9 Other (specify below) Welded Threaded Blank casing diameter 5 in. to 150 ft. Dia. in. to ft. Dia. in. to ft. Casing height above land surface 24 in., weight 2.902 lbs./ft. Wall thickness or gauge No. .265 SDR 21 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 7 PVC 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 10 Other (specify) 7 Torch cut SCREEN-PERFORATED INTERVALS: From 100 ft. to 150 ft. From ft. to ft. GRAVEL PACK INTERVALS: From 50 ft. to 150 ft. From ft. to ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug Grout intervals: From 1 ft. to 20 ft. From ft. to ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	3	TOP			
3	20	SANDY CLAY			
20	40	CLAY			
40	99	SANDY CLAY			
99	137	SAND			
137	150	CLAY			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-7-94 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KWWCL-430. This Water Well Record was completed on (mo/day/year) 4-7-94 under the business name of HOWARD DRILG.CO. BOX 806 BEAVER, OK 73932 by (signature) Howard

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.

#18394

OFFICE USE ONLY
T
R
EW
SEC
1/4
1/4
1/4