

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Grant		SW 1/4 NW 1/4 NE 1/4		10		T 30 S		R 38 E W	
Distance and direction from nearest town or city street address of well if located within city? From Ulysses - 9 Miles South, 5 Miles West, 4294 Ft. North, & 2610 Ft. West									
2 WATER WELL OWNER:		Elmer Hennigh T. Trust C/O John T. Clawson							
RR#, St. Address, Box # :		210 N. Simpson St.							
City, State, ZIP Code :		Ulysses, Kansas 67880							
		Board of Agriculture, Division of Water Resources Application Number: 391-7988-6602							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 486 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 200 ft. below land surface measured on mo/day/yr 5-18-90							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 30 in. to 486 ft., and in. to ft.							
		WELL WATER TO BE USED AS:							
		5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes.....No... X; If yes, mo/day/yr sample was submitted							
		Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued Clamped							
1 Steel		Welded X							
3 RMP (SR)		Threaded.....							
2 PVC									
4 ABS									
7 Fiberglass									
Blank casing diameter 16 in. to 350 ft., Dia		in. to ft., Dia							
Casing height above land surface 12 in., weight 42.05 lbs./ft.		Wall thickness or gauge No. 250							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC							
1 Steel		10 Asbestos-cement							
3 Stainless steel		11 Other (specify)							
2 Brass		12 None used (open hole)							
4 Galvanized steel									
5 Fiberglass									
6 Concrete tile									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped							
1 Continuous slot		6 Wire wrapped							
3 Mill slot		8 Saw cut							
2 Louvered shutter		9 Drilled holes							
4 Key punched		10 Other (specify)							
SCREEN-PERFORATED INTERVALS:		11 None (open hole)							
From 350 ft. to 486 ft., From		ft. to ft.							
GRAVEL PACK INTERVALS:		From ft. to ft.							
From 20 ft. to 486 ft., From		ft. to ft.							
From ft. to ft., From		ft. to ft.							
6 GROUT MATERIAL:		4 Other							
1 Neat cement									
2 Cement grout									
3 Bentonite									
Grout Intervals: From 0 ft. to 20 ft., From		ft. to ft., From ft. to ft.							
What is the nearest source of possible contamination:		10 Livestock pens							
1 Septic tank		14 Abandoned water well							
4 Lateral lines		11 Fuel storage							
7 Pit privy		15 Oil well/Gas well							
2 Sewer lines		12 Fertilizer storage							
5 Cess pool		16 Other (specify below)							
3 Watertight sewer lines		13 Insecticide storage							
6 Seepage pit									
9 Feedyard									
Direction from well? South		How many feet? 80							
FROM	TO	LITHOLOGIC LOG				FROM	TO	PLUGGING INTERVALS	
		See attached log							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was 1 constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 5-23-90 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 208 This Water Well Record was completed on (mo/day/yr) 6-22-90 under the business name of Minter-Wilson Drilling Co., Inc. by (signature) <i>nora keeler</i>									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-7320. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4