

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: GRANT		NE 1/4 NW 1/4 NW 1/4	25	T 30 S	R 38 E
Distance and direction from nearest town or city street address of well if located within city? Harshol Wells Farm MW-6					
2 WATER WELL OWNER:		Board of Agriculture, Division of Water Resources			
RR#, St. Address, Box #:		Application Number:			
City, State, ZIP Code:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL. 243' ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 226' ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 226.40' ft. below land surface measured on mo/day/yr 2-1-95			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter in. to ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes ☒ No ☒ ; If yes, mo/day/yr sample was submitted			
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued ☒ Clamped ☒			
1 Steel 3 RMP (SR)		Welded ☒			
2 PVC 4 ABS		Threaded ☒			
Blank casing diameter 4" in. to 213' ft., Dia.		in. to ft., Dia. in. to ft.			
Casing height above land surface 209' in., weight lbs./ft. Wall thickness or gauge No.					
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement			
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)					
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)			
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS:		From 213' ft. to 243' ft., From ft. to ft.			
GRAVEL PACK INTERVALS:		From 211' ft. to 243' ft., From ft. to ft.			
6 GROUT MATERIAL:		1 Neat cement 2 Cement grout 3 Bentonite 4 Other			
Grout Intervals: From 2.25' ft. to 209' ft., From 211' ft. to 209' ft., From ft. to ft.					
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well			
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage					
Direction from well? Southeast Northwest		How many feet? 100'			
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	0.5'	Topsoil			
0.5'	118'	CLAY, low to medium plasticity, Mod. brown			
118'	128'	CLAY, very fine, Mod. brown			
128'	208'	SAND, Fine to Med., well graded, yellowish			
208'	243'	Silty CLAY with SAND, Mod. brown - brown			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was ☒ (1) constructed, ☐ (2) reconstructed, or ☐ (3) plugged under my jurisdiction and was completed on (mo/day/year) **2-2-95** and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. **438** This Water Well Record was completed on (mo/day/yr) **2-2-95** under the business name of **KANSAS CITY TESTING LAB** by (signature) **Bernie Jone**