WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment→Division of Environment (Water well Contractors) Topeka, Kansas 66620

| 1. Location of well: | County | Fraction | | Section number | | Township number | Range number | | |
|--|--------------|--|---|--|---|---|----------------------------|--|--|
| | Stanton | SE _{1/4} SE _{1/4} SE | , | 13 | | T 30 s | R 39 | <u> [Ø</u> | |
| 2. Distance and direction from nearest town or city: from Big Bow99 m119.50wne south 2 east | | | | | | | | | |
| Street address of well location if in city- | | | | street: RFD 1 tate, zip code: Johnson, Ks. 67855 | | | | | |
| 4. Locate with "X" in section below: Sketch map: | | | | | 6. Bore hole dia. 914 in. Completion date | | | | |
| N Barn | | | | | | Well depth 300 ft. | 6/5/78 | | |
| 4. Locate with "X" in section below: Sketch map: Sketch | | | | | | 7Cable toolXRotary Driven Dug | | | |
| | | | | | | Hollow rod Jetted Bored Reverse rotary | | | |
| | | | | | | 8. Use: X_ Domestic Public supply Industry Irrigation Air conditioning Stock | | | |
| | | | | | | Lawn Oil field water Other | | | |
| | | | | | | 9. Casing: Material steel Height: Above of below Flued and Fluel Surface 18 in. | | | |
| t Lisin | | | | | | Threaded | | | |
| 1 Mile ———————————————————————————————————— | | | | | | Dia. 5_ in. to 270 ft. depth Wall Thickness: inches or | | | |
| 5. Type and color of material | | | | From | т _о | Diain. to ft. depth gage No320 | | | |
| Surface | | | | | | 10. Screen: Manufacturer's name | | | |
| Fine sand & lime shells | | | | 2 | 40 | Type styrene | Dia | | |
| Fine to coarse sand , lime shells w/clay break. | | | | 40 | 60 | Slot/gauze 1/16" Set between 270 | | | |
| Fine to coarse sandw/ gravel strips and Clay | | | | | | ft. a | nd | <u></u> fi.] | |
| breakers | | | | 60 | 195 | Gravel pack? Size ran | | | |
| Very fine sandy sand and brown clay | | | | 195 | 223 | 11. Static water level: | | day/уг. 78 | |
| Fine to coarse sand w/clay breakers & small | | | | | | 12. Pumping level below land | surfaces: | | |
| gravel | | | | 223 | 238 | | | I | |
| | | | | | | ft. after h Estimated maximum yield | , , EU | g.p.m. | |
| Very fine sand & brown clay | | | | 238 | 247 | 13. Water sample submitted: mo./day/yr. | | | |
| Coarse sand and small gravel | | | | 247 | 273 | | Date | | |
| Fine to coarse sand, large gravel and brown | | | | | | 14. Well head completion: Pitless adapter | 6 Inches above gro | ade | |
| sandrock | | | | 273 | 300 | 15. Well grouted? X | | ky | |
| | | | | | | With: X Neat cement | | ncrete ¬ | |
| | | | | | | Depth: From _0 ft. to _ | | $ O$ | |
| | | | | | | ft. <u>120</u> Direction <u></u> | ESE Type sept | ic nk | |
| | | | | ļ | | Well disinfected upon comple | | <u></u> ∿ | |
| | | | | | | 17. Pump: Manufacturer's name | X Not installed | عـ ا _" ا | |
| | | | | † | | Model number | _ HP Volts | | |
| | | | | | | Length of drop pipe Type: | _ ft. capacityg | ј.р.m. 🚱 гг | |
| | | | | | | Submersible | Turbine | | |
| (Use a second sheet if needed) | | | | | | Jet Centrifugal | Reciproco | ating Solite | |
| 18. Elevation: | 19. Remarks: | | | .1 | <u> </u> | 20. Water well contractor's c | | " ს | |
| | | | | | | This well was drilled under my | v jurisdiction and this re | eport | |
| · Topography: | | | | | | is true to the best of my knowledge and belief. Houck Bros. Drlg. Co. 164 | | | |
| Hill | | | | | | Business name 487. U | | ise No. | |
| Upland | | | | | | Address Book | 2 / | 111. 120 PM | |
| | | | | | | | | ~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~ | |