		WELL RECORD F	orm WWC-5	KSA 82a-	1212			
LOCATION OF WATER WELL:	Fraction	M == .:		n Number	Townsh	ip Number	Range	Number
County: Symner	55 1/4		U 1/4	4	Т	3 ℃s	R	4 EW
Distance and direction from nearest town	or city street add	dress of well if located	within city?	•				_
Suppesville								
WATER WELL OWNER: STOVE	IIMH 3						-	
R#, St. Address, Box # : 1426	N. Roger	5			Board	of Agriculture,	Division of W	/ater Resourc
	on. Ks. 6					ation Number:	DIVISION OF V	rater riesoure
IN STATE WELLS CONTINUE	p_{N_1} N_2 . φ	Πυφ	771		Applic	ation Number.		
LOCATE WELL'S LOCATION WITH 4 AN "X" IN SECTION BOX:	DEPTH OF CO	MPLETED WELL		ft. ELEVAT	ΓΙΟΝ:			
ALL X III SECTION BOX:	epth(s) Groundw	ater Encountered 1	<u></u>	. 📆 🛴 . ft. 2		,🎝 , 🔁 ft. 3	3	
l l	VELL'S STATIC V	VATER LEVEL	. i.:2 , ft. beld	ow land surf	ace measure	d on mo/day/yr	10-1	Ø. ~.7 <i>"7</i> "
	Pump	test data: Well water	was	ft. af	ter	hours ou	ımpina	
NW NE _E		gpm: Well water					_	
1 ' 1 ' 1 ' -		er						
W								
	VELL WATER TO					oning 11	-	
SW -X SE	1 Domestic					12		
	2 Irrigation					well		
	Vas a chemical/ba	acteriological sample su	bmitted to Dep	artment? Ye	sNo	X; If yes	, mo/day/yr s	ample was su
	nitted					fected? Yes X		•
TYPE OF BLANK CASING USED:		5 Wrought iron	8 Concrete	tile	CASING	G JOINTS: Glue	d X Cl	amped
1 Steel 3 RMP (SR)		6 Asbestos-Cement					•	
				-				
2 PVC 4 ABS		7 Fiberglass フル				Thre	aded	
lank casing diameter	n. to	スイft., Dia	in. to .		ft., Dia .		in. to	
asing height above land surface	. 18 i	n., weight		Ibs./f	t. Wall thickr	ess or gauge N	10	. ≪
YPE OF SCREEN OR PERFORATION	MATERIAL:		7 PVC	_	10	Asbestos-ceme	ent	
1 Steel 3 Stainless s	steel	5 Fiberglass	8 RMP	(SR)	11	Other (specify)		
2 Brass 4 Galvanized		6 Concrete tile	9 ABS	` ,	12	None used (or	pen hole)	
CREEN OR PERFORATION OPENING			d wrapped		8 Saw cut	٠.	,	open hole)
1 Continuous slot 3 Mill					9 Drilled h	_	TT THORIC (open noie,
			rapped					
2 Louvered shutter 4 Key	punched	34 ⁷ Torch o	cut n	14	10 Other (s	pecify)		
CREEN-PERFORATED INTERVALS:	From	. ? . 7 . ft. to		7ft., Fron	n	ft. 1	to	
	From	<u>.</u> . _. . ft. to		ft., Fron	n , , ,	ft. [.]	to	
GRAVEL PACK INTERVALS:	From	.24 . ft. to		H ft From	n	ft. [.]	to	
	_	•		•		ft.		
GROUT MATERIAL: 1 Neat ce		Çement grout						
Grout Intervals: From	5	" Francisco	3 Bernon	4				
		H. ft., From	π. το					
What is the nearest source of possible co				10 Livest	ock pens	14 <i>F</i>	Abandoned v	ater well
1 Septic tank 4 Lateral	eptic tank 4 Lateral lines			11 Fuel storage		15 Oil well/Gas well		
2 Sewer lines 5 Cess p	loool	8 Sewage lagoo	on	12 Fertili	zer storage	16 (Other (specify	y below)
3 Watertight sewer lines 6 Seepag	ge pit	9 Feedyard		13 Insec	ticide storage			
irection from well? N W	5 - F -				ny feet? 30			
FROM TO	LITHOLOGIC L	OG	FROM	TO	iy leet: J	PLUGGING	INTERVALS	
	LITTIOLOGIO L	00	1110101			7 2000		
0 2 50:1	a		 					
2 10 Fine >	dNC ₁		 					
10 21 Gray C	lay							
21 22 Find S	and							
22 34 Red C	1000							
		1	1					
34 74 Red SI	WALL -		 					
			+					
			 					
			1					
			 - - - - - - - -					
			1					
			1 '					
	773 M							
CONTRACTOR'S OR LANDOWNERS	S CEDTICIOATIO	NI. This water well as	(1) 2022	od (2)	notriole 4	(2) plugged :	dor my hyda	diction and
in in	S CERTIFICATIO	ON: This water well wa	-					
ompleted on (mo/day/year)	S CERTIFICATIO		a	nd this reco	rd is true to t	he best of my ki		
ompleted on (mo/day/year)	s certification	ON: This water well wa	a	nd this reco	rd is true to t	he best of my ki		
ompleted on (mo/day/year)	s certification 10 - 17 - 17 - 17 - 17 - 17 - 17 - 17 -		a	nd this reco	rd is true to t on (mo/day/y	he best of my ki		