| WATER WELL RECORD F | orm WWC-5 I | KSA 82a-1212 | |
|--|--|--|---------------------------------------|
| 1 LOCATION OF WATER WELL: FRACTION | SECTION NUMBE | | RANGE NUMBER |
| Sumner NW 1/4 NW 1/4 NW | 1/4 10 | T 30 S | R 4W E/W |
| Distance and direction from nearest town or city street address of well if located within city? | accerilla on V 42 I | (J) | |
| 1623 W. 140th Milton, Kansas (1/2 mile E. of Supplement of | besville on K-42 i | iwy) | |
| RR#,ST. ADDRESS,BOX #: 1717 Elk Ridge | | Board of Ag | riculture, Division of Water Resource |
| CITY, STATE: Goddard, Kansas | ZIP CODE: | Application Nu | mber: |
| 3 LOCATE WELL'S LOCATION 4 DEPTH OF COLLEGE VELL: 10 | | ELEVATION: grade | |
| WITH AN "X" IN SECTION BOX: | ft. | ft. | ft. |
| WELL'S STATIC WATER LEVEL | | SURFACE MEASURED ON mo/ | _ |
| Pump test data: Well wat | | | s of pumping @ gpn |
| | ter was | | s of pumping @ gpm |
| Est. Yield: gpm Well wa | to f | t, and in. | to ft. |
| WELL WATER USED AS: | | 9. Dewater | ing 11. Injection well |
| 1. Domestic 3. Feedlot 5. Public wa | | and garden only | 12. Other (Specify below |
| 2. Irrigation 4. Industrial 6. Oil field w Was a chemical/bacteriological sample submitted to I | | onditioning 10. Monitori NO ; If yes, | what mo/day/yr was sample |
| S Was a chemical/bacteriological sample submitted to I submitted | | Water Well Disinfected? | YES NO |
| TYPE OF CASING USED: 5. Wrought Iron 7. Fiberglass | 9. Other (Speci | fy below) CASING JOINTS: | Glued Threaded |
| 1. Steel 3. RPM (SR) | | • | Welded Clamped |
| 2. PVC 4. ABS 6. Asbestos-Cement 8. Concrete to | | | |
| Blank casing diameter 5 in. to 100 ft., Dia. | in. to | ft., Dia. | in. to ft. |
| Casing height cash and surface: 12 in., Weight: | lbs. / ft. | Wall thickness or gau | ge No. |
| TYPE OF SCREEN OR PERFORATION MATERIAL: | | 11. Other (specify) | N/A |
| 1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC | 9. ABS | | |
| 2. Brass 4. Galvanized 6. Concrete Tile 8. RMP (SR) | 10. Asbestos-Ce | ement 12. None used (oper | nole) |
| SCREEN OR PERFORATION OPENINGS ARE: | - · · | 0. 8. 40 4.5 1 | 44 None (bols) |
| 1. Continuous slot 3. Mill slot 5. Gauzed wrapped | 7. Torch cut | 9. Drilled holes | 11. None (open hole) |
| 2. Louvered shutter 4. Key punched 6. Wire wrapped | 8. Saw cut | 10. Other (specify) N | 1/A |
| SCREEN - PERFORATION INTERVAL From ft. to | ft., | From ft. | to ft. |
| From ft. to | ft., | From ft. | to ft. |
| GRAVEL PACK INTERVALS: From ft. to | ft., | From ft. | to ft. |
| From ft. to | ft., | From ft, | to ft. |
| 6 GROUT MATERIALS: 1. Neat cement 2. Cement Grout | 3. Bentonit | e Other ben | tonite hole plug |
| Grout Intervals: From 3 ft. to 28 ft., From | ft. to | ft., From | ft. to ft. |
| What is the nearest source of possible contamination: | 0. Livestock pens | · | 15. Oil well/Gas well |
| 1. Septic tank 4. Lateral lines | · | 13. Insecticide storage | 16. Other (specify below) |
| 2. Sewer lines 0. Scall out | 11. Fuel storage | 14. Abandon water well | To. Other (specify below) |
| 5. Water ugit sewer mile | 12. Fertilizer storage | 11 |) ft mluc |
| Direction from well? Northeast From To LITHOLOGIC LOG | From To | How many feet? 200 | OGIC LOG |
| TIGHT TO ETTHOLOGIC LOG | 0 3 | natural earth backfill | JGIC LOG |
| | 3 28 | bentonite hole plug | |
| | 28 100 | chlorinated sand and | gravel |
| | <u> </u> | | |
| | | | |
| | + + + | <u> </u> | |
| | 1 | | |
| | | | |
| | | | |
| | <u> </u> | | |
| | + + + | 1 | |
| | | - | |
| | + + + - | <u> </u> | |
| 7 Contractor's or Landowner's Certification: This water well was 1. constructed | 1 0 *********************************** | od or 2 nlugged | under my jurisdiction and |
| | | | |
| | | y knowledge and belief. | |
| Kansas Water Well Contractor's License No. 236 This water well record was completed on (mo/day/year) 8/2/2011 | | | |
| under the business name of Harp Well and Pump Service by (signature) Todd S. Harb | | | |