INSTRUCTIONS: Please fill in blanks Jackson St., Ste. 420, Topeka, Kansas	s and circle the correct answers. Send to s 66612-1367. Telephone: 913-296-55	hree copies to Kans 45. Send one to WA	as Departmer	it of Health and Environm DWNER and retain one fo	nent, Bureau of Vor your records.	Vater, 1000 S V	V
under the business name of	Geotechnical Services In	nc. bv	(signature)	A. K. Ila			
Water Well Contractor's License No.				cord was completed o			
completed on (mo/day/yr)	09/28/11			ue to the best of my ki			I
7 CONTRACTOR'S OR LANDOWNER	₹'S CERTIFICATION: This water we	ell was (1) construc	ted, (2) reco	nstructed, or (3) plugge	d under my iuri	sdiction and w	as
				Lasung. 1941 18			
				Northing: 16051 Easting: 154119			
				GPS:	10.04	····	
				CDC.	***************************************		
	WENT OF THE PARTY	-	1				
	The state of the s		-				
21 28 sc Cla	ayey Sand, red-brown			Restaurant de la companya de la comp			
0 21 CL 16'	way Canal		-				
grav	vel between 6' and 16', sand len						P
	an Clay, red-brown, some san		+ -	FLOGG	HAO HATERVA		
FROM TO CODE	LITHOLOGIC LOG	FROM	TO TO		ING INTERVA	IS	
Direction from well?	6 Seepage pit 9 Fee	suyaru	How many	ticide storage			
Sewer lines Watertight sewer lines		wage lagoon			16 Other (spec	city below)	
1 Septic tank 2 Sewer lines	4 Lateral lines 7 Pit			·	15 Oil well/ Ga		
What is the nearest source of possible o	contamination:		10 Lives	tock pens	14 Abandoned	water well	
Grout Intervals From 2	ft. to 15 ft. From	ft. t	0	ft. From	ft. to		ft.
6 GROUT MATERIAL: 1 Neat of	ement 2 Cement grout	3 Ben	tonite	4 Other			
			ft. F		ft. to		ft.
GRAVEL PACK INTERVALS:	From 15 ft. to	28	ft. F	rom			ft.
ODANEL DAOMATERMA	From ft. to		ft. F	rom	ft. to		ft. 🗖
SCREEN-PERFORATED INTERVALS:		21.3	ft. F	rom	ft. to		ft.
		Torch cut		10 Other (specify)			
Paracata Integra	A STATE OF THE PARTY OF THE PAR	Wire wrapped		9 Drilled holes			
SCREEN OR PERFORATION OPENING	CONTROL OF THE PROPERTY OF THE	Gauzed wrapped		8 Saw cut	11 Nor	ne (open hole)).
	nized steel 6 Concrete tile	9	ABS	12 None use	ed (open hole)		
1 Steel 3 Stainle	9	8	RMP (SR)	11 Other (sp	pecify)		
TYPE OF SCREEN OR PERFORATION	N MATERIAL:	7	PVC	10 Asbestos	s-cement	******	
Casing height above land surface	28 in., weight	0.703	lbs./ft.	Wall thickness or gau	ge No.	SCH. 40	
Blank casing diameter 2	in. to 17.3 ft., Dia	in. t	0	ft., Dia	in. to		ft.
2 PVC 4 ABS	7 Fiberglass				Threaded		
1 Steel 3 RMP (S	•	ement 9 Other	(specify belo	annichte Antheoreachaean annach	Welded	tite dalam se sensors galarine conserva	mentana mana
5 TYPE OF BLANK CASING USED:	5 Wrought Iron			CASING JOINTS:	Glued	Clamped	
	submitted			ter Well Disinfected?			
_	Was a chemical/bacteriological sam						s
	2 Irrigation 4 Industrial						
	1 Domestic 3 Feed lot	6 Oil field water	supply	9 Dewatering	12 Other	(Specify below	w)
swse	Bore Hole Diameter 8.25 in WELL WATER TO BE USED AS: 1 Domestic 3 Feed lot	5 Public water st	nbbla	8 Air conditioning	11 Injecti	on well	£
	Bore Hole Diameter 8.25 in	, to 28	3	ft. and	in. to	9r	ft. CN
E W	Est. Yield gpm: Well	water was	f	t. after	nours numping	ar	m 17
	Pump test data: Well						j i
	WELL'S STATIC WATER LEVEL						ft. C
1	Depth(s) Groundwater Encountered	d 1 2 1	ft	. 2	ft. 3		Ç
3 AN "X" IN SECTION BOX:	DEPTH OF COMPLETED WEL	L 27.	3 ft. ELE	/ATION:	1383.64 (T	OC)	
City, State, ZIP Code : Wichita LOCATE WELL'S LOCATON WITH	T	***************************************	***************************************	Application Number	er:		
RR#, St. Address, Box # : 53000 l		MAFB		Board of Agricultu	re, Division of V	Water Resourc	ces
2 WATER WELL OWNER: 22 nd CE		1 # 0 manus					
3 miles west of Viola on K-42						***************************************	
Distance and direction from nearest town							
County: Sumner	NE ¼ NW ¼	SW 1/4	1	т 30	S R	, P**	W
1 LOCATION OF WATER WELL:	Fraction	Sec	tion Number	***************************************	er l Ra	nge Number	
	WATER WELL RECORD	Form WWC-5	KSA 82a-1	212 ID No.			