Locat	ION OF WA	ren wez	FRACTION	Water Well Record	Form WWC-5	KSA 82a-1212	T	DN	
1	ion of wa S umne		NW 1/4	SE 1/4 NW	1 1/4	Section Number	Township Number	Range Number	
			y street address of well if loca		1/4	*	T 30 8	R 4M E/W	
	t #6	Reserve		sville Gol	f Cour	so Mi	lton, Kansas		
	ER WELL O		ER, Mike	SATTLE GOT	1 COUL	se mi.	LUII, KAIISAS		
RR#, S	T. ADRESS,		•	e B			Board of Agriculture,	Divivsion of Water Resource	
CITY, STATE, ZIP CODE: Milton, Kansas						Application Number:			
		OCATION WITH		APLETED WELL	90	ft. ELE	VATION:		
	IN SECTION	BOX:	Depth(s) groundw	ater Encountered	1	ft.	2 ft.	3 ft.	
1			WELL'S STATIC W	ATER LEVEL 20	FT. I	BELOW LAND SUR	FACE MEASURED ON mo/day/yr	01/20/1994	
·	NW,	NE	Pump tes	t data: Well wa	ter was	ft. s	after hours pu	mping gpm	
<u>ə</u>	λ.		Est. Yield	gpm: Well wa			after hours pu		
1Mile A		E	Bore Hole Diameter	12 in. to	90 Public water:	ft.	and in	, to ft. Injection well	
			WELL WATER TO I 1 Domestic		Oil field water			Other (Specify below)	
	sw	SiE	2 Irrigation		Lawn and ga		0 Monitoring well		
								mo/day/yr sample was	
		S	submitted				er Well Disinfected? Yes	X No	
5 TYP	E OF CA	SING USED:		5 Wrought iron	8 (Concrete tile	CASING JOINTS:	Glued X Clamped	
1 Steel		3 RMP (SR)		6 Asbestos-Cement	90	Other (Specify be	elow)	Welded	
2 PVC	_	4 ABS		7 Fiberglass	SI	R-26		Threaded	
	sing Diam	•	in. to 25	ft., Dia	in.	to	ft., Dia in.	to ft.	
	_	e land surface 1 N OR PERFORA	L 2 in. , TION MATERIAL:	weight 2.	J J	lbs. / ft. PVC	Wall thickness or gauge No. 10 Asbestos-ce	.214 ment	
1 Stee		3 Stainless Steel	TO NATI DILLE	5 Fiberglass	-	RMP (SR)	11 other (speci	ify)	
2 Brass 4 Galvanized steel 6 Concrete tile					9.	ABS 12 None used (open hole)			
SCREE	SCREEN OR PERFORATION OPENING ARE: 5 Gauzed w					8 Saw cut 11 None (open hole)			
1 Continous slot 3 Mill slot 6 Wire wrap						oped 9 Drilled holes			
2 Louve	red shutte	r 4 Key p	unched	7 Torch	eut		10 Other (specify)		
SCREEN-PERFORATION INTERVALS: from 25 ft. to 90 ft., From ft. to									
from ft. to					o	ft., From		o ft.	
GRAVEL PACK INTERVALS: from 24 ft. to					to 90	ft., Fron	n ft. t	to ft.	
		4.37	from	ft. 1		ft., Fron		<u>o</u> <u>ft.</u>	
	UT MAT		_	Cement grout	3 Ben		4 Other		
Grout Intervals: From 4 ft. to 24 ft. From What is the nearest source of possible contamination:					ft. t	to ft. From ft. to ft. 10 Livestock pens 14 Abandon water well			
1 Septic tank 4 Lateral lines 7 Pit privy						11 Fuel storage 15 Oil well/Gas well			
2 Sewer lines 5 Cess pool 8 Sewage lagoor					n	12 Fertilizer storage 16 Other (specify below)			
3 Watertight sewer lines 6 Seepage pit 9 Feedyard						13 Insecticide storage			
Direction from well? Northwest How many feet? 33									
FROM			LITHOLOGIC LOG		FROM	то	PLUGGING INT	ERVALS	
0	3	topsoil			_				
3	12	clay				 			
12 20	20 90	fine sar			 				
20	90	red Sha.	Ta						

					<u> </u>				
7 CON	ITD A CTT	NDIS or		nie woter wall was 14	\ nonetricate	d /2\ racasst	uotad or /2\ plucasd und	r my juriediction and	
	(TKACI'()mpleted	on (mo/day/year	ck's CERTIFICATION: TI r) 01/20/	11994 water well was (1	onstructe	ord is true to t	ucted, or (3) plugged unde he best of my knowledge a	nd belief, Kansas Water	
Well C	ontracto	r's License No	236	This Water Well Re	cord was co	mpleted on (n	no/day/yr)Q1./	21/94	
Under	the busi	ness name ofH	arp Well &	Pump		by (sigr	nature)		
						_	Jane	Frederick	