			WATER	R WELL RECORD	Form WWC-5	KSA 828	a-1212	
_		TER WELL:	Fraction		1	tion Number		Range Number
County:	SUMNER		NW 1/4	NW 1/4	NW 1/4	11	T 30 S	R 4 W 1E/W
			-	dress of well if locat	•			
				Suppesvill	e, Ks.			
-	WELL OW		lore M. Hill					
		* # : P.O.					Board of Agriculture,	Division of Water Resources
City, State,	ZIP Code	: Norwi	ch, Kansas	67118			Application Number:	
LOCATE	WELL'S LOIN SECTION	OCATION WITH	4 DEPTH OF CO	OMPLETED WELL	67	ft. ELEVA	ATION:	
AN A	IN SECTION	N BOX.	Depth(s) Groundw	vater Encountered	1 25	ft.	2 ft.	3
ī X	!	i i	WELL'S STATIC	WATER LEVEL	25 ft. b	elow land su	rface measured on mo/day/y	r 5-8-84
i L	- NW	NE	Pump	test data: Well wa	ter was	ft. a	after hours p	umping gpm
	1	1,40	Est. Yield	gpm: Well wa	ter was	ft. a	after hours p	umping gpm
_≘ w ⊢	į	1 .	Bore Hole Diamet	ter $1.4\ldots$ in. to	o	ft.,	and	n. to
₹ " [1	WELL WATER TO	D BE USED AS:	5 Public water	r supply	8 Air conditioning 11	Injection well
7	- sw	SE	1 Domestic	3 Feedlot	6 Oil field wa	ter supply	9 Dewatering 12	Other (Specify below)
-	- 344	35	2 Irrigation	4 Industrial	7 Lawn and g	arden only	10 Observation well	
1 1	i i	i	Was a chemical/b	acteriological sample	submitted to De	epartment? Y	'es; If ye	s, mo/day/yr sample was sub
			mitted			Wa	ater Well Disinfected? Yes	X No
5 TYPE C	F BLANK	CASING USED:		5 Wrought iron	8 Concre	ete tile	CASING JOINTS: Glue	ed . X Clamped
1 Ste	eel	3 RMP (S	R)	6 Asbestos-Cement	9 Other	(specify belo	w) Wel	ded
2 PV	C	4 ABS		7 Fiberglass	Cer-Ma	ac styre	ne SDR-26 Thre	eaded
Blank casir	ng diameter		.in. to 2.7	ft., Dia			ft., Dia	
							/ft. Wall thickness or gauge I	
		R PERFORATIO		-	7 PV		10 Asbestos-cem	
1 Ste	el	3 Stainless	s steel	5 Fiberglass	8 RM	IP (SR)	11 Other (specify	()
2 Bra	ass	4 Galvaniz	ed steel	6 Concrete tile	9 AB	===== S	12 None used (d	pen hole)
SCREEN (OR PERFOR	RATION OPENIN	IGS ARE:	5 Gau	zed wrapped		8 Saw cut	11 None (open hole)
1 Co	ntinuous slo	t 3 M	lill slot	6 Wire	wrapped		9 Drilled holes	, , ,
2 Lo	uvered shut	ter 4 K	ey punched	7 Toro	ch cut		10 Other (specify)	
SCREEN-F	PERFORATI	ED INTERVALS:	From	27 ft. to	67	ft., Fro	om ft.	toft.
				- ·			om ft.	
G	RAVEL PA	CK INTERVALS:					om ft.	
			From	ft. to	٠.	ft., Fro		to ft.
	MATERIAL		cement 2	2 Cement grout	3 Bento	nite 4	Other	
Grout Inter	vals: Fro	m 4	. ft. to 1.4	ft., From	ft.	to	ft., From	ft. to
		ource of possible		,				Abandoned water well
1_Se	ptic tank	4 Later	ral lines	7 Pit privy			•	Oil well/Gas well
1 Septic tank 4 Lateral lines 2 Sewer lines 5 Cess pool				8 Sewage lagoon		12 Fertilizer storage 16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage								
Direction for		Southwest		- · · · · · , - · · ·			any feet? 89	
FROM	TO		LITHOLOGIC L	_OG	FROM	ТО	LITHOLO	GIC LOG
0	3	Topsoil						
3	17	Fine Sand	1					
17	32	Fine Sand	l & Clay Bal	.1s				
32	39	Clay						
39	45	Fine Sand	i					
45	67	Red Shale						
			-					
7 00117	LACTORIO	00 1 4410014	D'O CEDTIFICATI	ONL This was "	- (1) - :	I		- d
							onstructed, or (3) plugged ur	
							ord is true to the best of my k	
							on (mo/day/yr)	31-84
under the	business na	me of Harp	Well & Pump	Service, In	C.	by (signa	ature) Mary (unica)
three conic	i iUNO: USB es to Kanese	Department of L	point pen, <u>PLEASI</u>	ent Division of Envir	onment Environ	iy. Miease fill mental Goole	in blanks, underline of circle togy Section, Topeka, KS 6662	THE COTTECT ANSWERS. SEND TOP
OWNER a	nd retain o	ne for your recor	ds.	ion, Division of Enviro	Januari, Environ	memai Geol	yy Jeonon, Topeka, No 60021	. Send one to WATER WELL