


1 LOCATION OF WATER WELL:		Fraction	Section Number		Township Number	Range Number
County: SUMNER		SW 1/4 NW 1/4 SW 1/4	21		T 30 S	R 4 W EW
Distance and direction from nearest town or city street address of well if located within city? approximately 3/4 South of Milton, KS. on the east side of the road.						
2 WATER WELL OWNER:		Ann Van Volkenberg				
RR#, St. Address, Box # :		Box 296				
City, State, ZIP Code :		Conway Springs, KS. 67031				
Board of Agriculture, Division of Water Resources		Application Number: 38379				
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 82 ft. ELEVATION: 26 ft.				
N 1 Mile W E S 		Depth(s) Groundwater Encountered 1. 26 ft. 2. 3. 4-20-87 ft.				
		WELL'S STATIC WATER LEVEL 26 ft. below land surface measured on mo/day/yr				
		Pump test data: Well water was ft. after hours pumping gpm				
		Est. Yield gpm: Well water was ft. after hours pumping gpm				
Bore Hole Diameter 30 in. to ft., and in. to ft.		WELL WATER TO BE USED AS:				
1 Domestic		3 Feedlot		6 Oil field water supply		9 Dewatering
2 Irrigation		4 Industrial		7 Lawn and garden only		10 Observation well
Was a chemical/bacteriological sample submitted to Department? Yes No X		If yes, mo/day/yr sample was submitted				
5 TYPE OF BLANK CASING USED:		5 Wrought iron		8 Concrete tile		CASING JOINTS: Glued Clamped X
1 Steel		3 RMP (SR)		6 Asbestos-Cement		9 Other (specify below)
2 PVC		4 ABS		7 Fiberglass		10 Asbestos-cement
Blank casing diameter 16 in. to 43 ft., Dia		in. to ft., Dia		in. to ft., Dia		11 Injection well
Casing height above land surface 12 in., weight 37 lbs./ft. Wall thickness or gauge No. 3/4"		12 Other (Specify below)				
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC		10 Asbestos-cement		Transite
1 Steel		3 Stainless steel		5 Fiberglass		8 RMP (SR)
2 Brass		4 Galvanized steel		6 Concrete tile		9 ABS
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped		8 Saw cut		11 None (open hole)
1 Continuous slot		3 Mill slot		6 Wire wrapped		9 Drilled holes
2 Louvered shutter		4 Key punched		7 Torch cut		10 Other (specify)
SCREEN-PERFORATED INTERVALS:		From 43 ft. to 82 ft., From		ft. to ft. to ft. to		
GRAVEL PACK INTERVALS:		From 10 ft. to 82 ft., From		ft. to ft. to ft. to		
6 GROUT MATERIAL:		1 Neat cement		2 Cement grout		3 Bentonite
Grout Intervals: From 0 ft. to 10 ft., From		ft. to ft. to		ft. to ft. to		
What is the nearest source of possible contamination:		1 Septic tank		4 Lateral lines		7 Pit privy
2 Sewer lines		5 Cess pool		8 Sewage lagoon		10 Livestock pens
3 Watertight sewer lines		6 Seepage pit		9 Feedyard		11 Fuel storage
Direction from well?		How many feet?		12 Fertilizer storage		14 Abandoned water well
13 Insecticide storage		None Apparent		15 Oil well/Gas well		16 Other (specify below)
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG		
0 5 Topsoil						
5 15 Fine Sand						
15 36 Fine to Medium Sand						
36 40 Fine sand with Clay Streaks						
40 61 Medium Sand						
61 82 Medium to Coarse Sand						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 4-20-87 and this record is true to the best of my knowledge and belief. Kansas						
Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 6-10-87						
under the business name of Harp Well & Pump Service, Inc. by (signature) Mary Arnold						
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water Protection, Topeka, Kansas 66620-7320, Telephone: 913-862-9360. Send one to WATER WELL OWNER and retain one for your records.						

OFFICE USE ONLY

T

R

EW

SEC.

1/4

1/4

1/4