

1 LOCATION OF WATER WELL:		FRACTION		Section Number		Township Number		Range Number	
Sumner		NW 1/4 NW 1/4 NE 1/4		32		T 30 S		R 4W E/W	
Distance and direction from nearest town or city street address of well if located within city?									
2 m. S. of Milton, Ks., 1/2 W. of Hwy., S. side Milton, Ks.									
2 WATER WELL OWNER:		CALLAHAN, Victor							
RR#, ST. ADDRESS, BOX #:		RR #1							
CITY, STATE, ZIP CODE:		Milton, Kansas 67106							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL 60 ft. ELEVATION:							
		Depth(s) groundwater Encountered 1 ft. 2 ft. 3 ft.							
		WELL'S STATIC WATER LEVEL 35 FT. BELOW LAND SURFACE MEASURED ON 08/10/1992							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 12 in. to 60 ft., and in. to ft.							
		WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well							
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)							
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well							
		Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was submitted							
5 TYPE OF CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR)		Welded							
2 PVC 4 ABS		Threaded							
Blank casing Diameter 5 in. to 35 ft., Dia in. to ft.		SDR-26							
Casing height above land surface 12 in., weight 2.35 lbs. / ft.		Wall thickness or gauge No. .214							
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 11 other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENING ARE:		8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 5 Gauzed wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 6 Wire wrapped 10 Other (specify)									
SCREEN-PERFORATION INTERVALS:		from 35 ft. to 60 ft., From ft. to ft.							
GRAVEL PACK INTERVALS:		from 24 ft. to 60 ft., From ft. to ft.							
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From 4 ft. to 24 ft., From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandon water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? NE		How many feet? 120							
FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
0 3 topsoil									
3 31 sandy clay									
31 40 fine sand									
40 45 medium sand									
45 60 red shale									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 08/10/1992 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 236 This Water Well Record was completed on (mo/day/yr) 11/05/92 Under the business name of Harp Well & Pump Service, Inc. by (signature) Jane Frederick									
221									