


1 LOCATION OF WATER WELL: County: Stanton		Fraction SW SW 1/4 SE 1/4		Section Number X 9	Township Number T 30 S	Range Number R 40 E/W
Distance and direction from nearest town or city street address of well if located within city? Co. Line N. of Richfield: 4N, 3 1/2 E, N. into						
2 WATER WELL OWNER: Seaboard Farms RR#, St. Address, Box #: P.O. Box 1207 City, State, ZIP Code: Guyton, OK. 73942				Farm #238 Board of Agriculture, Division of Water Resources Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL: 440 ft. ELEVATION: Depth(s) Groundwater Encountered: 1 211 ft. 2. 211 ft. 3. 211 ft. WELL'S STATIC WATER LEVEL: 211 ft. below land surface measured on mo/day/yr 07-03-96 Pump test data: Well water was 350 ft. after 1 hours pumping 100 gpm Est. Yield: 100 gpm: Well water was 350 ft. after 1 hours pumping 100 gpm Bore Hole Diameter: 11 in. to 440 ft. and 440 in. to 440 ft. WELL WATER TO BE USED AS: 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 11 Injection well 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Hogfarm 12 Other (Specify below) Was a chemical/bacteriological sample submitted to Department? Yes X No X ; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes X No				
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter 6 in. to 440 ft. Dia 24 in. to 2.902 lbs./ft. Wall thickness or gauge No. .280 SDR21 Casing height above land surface 24 in. weight 2.902 lbs./ft. Wall thickness or gauge No. .280 SDR21 TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot 3 Mill slot 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From 360 ft. to 440 ft. From 360 ft. to 440 ft. GRAVEL PACK INTERVALS: From 240 ft. to 440 ft. From 240 ft. to 440 ft.						
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Hole Plug Grout Intervals: From 0 ft. to 16 ft. From 0 ft. to 16 ft. From 0 ft. to 16 ft. From 0 ft. to 16 ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS 0 2 Clay 243 284 Blue, Red, Sandy Clay 2 42 Clay 284 300 Blue Clay 42 50 Clay & Sandy Clay 300 365 Black & Blue Clay 50 90 Clay 365 370 Sandy Clay & Fine Sand 90 127 Clay & Sandy Clay 370 387 Fine Sand 127 137 Sandy Clay 387 402 Black Sandy Clay 137 162 Sand 402 415 Black & Blue Clay 162 167 Sandy Clay 415 440 Black Clay & Sand Stone 167 173 Clay 173 179 Sandy Clay 179 187 Clay 187 224 Sand 224 227 Clay 227 236 Sand 236 243 Caliche Clay						
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-18-1999 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. KMCL-430 This Water Well Record was completed on (mo/day/yr) 7-03-96 under the business name of Howard Drilling, Box 806, Beaver, OK. 73932 by (signature) <i>[Signature]</i>						