WATER	R WELL RECORD	Form WWC-!	5 KSA 82a-	-1212			
1 LOCATION OF WATER WELL: Fraction	· ····································		ction Number	Township N	umber	Range	Number ,
County: Stanton NW 1/4		NE 1/4	10	т 30	S	R 40	E (()
Distance and direction from nearest town or city street ac		-					
7 miles south and 4 miles east of	Johnson, Kans	as.					5
2 WATER WELL OWNER: Kirby Clawson							
RR#, St. Address, Box # :	•			Board of A	griculture, [Division of Wa	ter Resources
City, State, ZIP Code : Satanta, KS 6787	0 .			Application	Number:		
DEPTH OF CO	OMPLETED WELL	615	ft. ELEVA	TION:			
N Depth(s) Groundy	vater Encountered 1.						
X WELL'S STATIC	WATER LEVEL 24	5 ft. t	elow land surf	face measured on	mo/day/yr	3-11-86	
NW NE Pump	test data: Well water	was . 4.60) ft. af	íter . 4	hours pur	mping . 814	gpm
Est. Yield	gpm: Well water	' was	ft. af	ter	hours pur	mping	gpm
	ter24in. to . O BE USED AS:						
1 Domestic		5 Public water		8 Air conditioning 9 Dewatering		njection well	
SW SE 2 Irrigation				Observation we		Other (Specify	
	acteriological sample s						mole was sub
s mitted	actoriological cample s	ubililitied to D		ter Well Disinfecte			X
	5 Wrought iron	8 Concr		CASING JOI			
1 Steel 3 RMP (SR)	6 Asbestos-Cement		(specify below				
	7 Fiberglass			•			
Blank casing diameter	ft., Dia	in. to		ft Dia	i	n. to	ft.
Casing height above land surface12	in., weight	2.05	Ibs./f	t. Wall thickness o	or gauge No	250	
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PV			estos-ceme		1
	5 Fiberglass	8 RN	IP (SR)	11 Oth	er (specify)		
	6 Concrete tile		_		e used (ope	•	
SCREEN OR PERFORATION OPENINGS ARE:						11 None (or	pen hole)
1 Continuous slot 3 Mill slot		rapped		9 Drilled holes			1
2 Louvered shutter 4 Key punched SCREEN-PERFORATED INTERVALS: From . 263	7 Torch		e. ==	10 Other (specify	")		
From 300-	283ft. to .3	.99.559 00 - 615	π., From	n	ft. tc)	
GRAVEL PACK INTERVALS: From 10-	615 ft. to	.,,,,,,,,,,,	ft From	П	π. το)	π. ₄ .
From	ft. to		ft From	<u>n</u>	ft to		ft.
6 GROUT MATERIAL: 1 Neat cement 2	2 Cement grout	3 Bento		Other			
Grout Intervals: From				ft., From		. ft. to	
What is the nearest source of possible contamination:			10 Liveste			andoned wat	1
1 Septic tank 4 Lateral lines	7 Pit privy		11 Fuel s	storage	15 Oi	well/Gas we	H
2 Sewer lines 5 Cess pool	8 Sewage lago	on		zer storage		her (specify t	
3 Watertight sewer lines 6 Seepage pit	9 Feedyard			icide storage	.None.o	bserved.	
Direction from well? FROM TO LITHOLOGIC L	00		How man				
THOM TO ETHOLOGIC L	.00	FROM	ТО		LITHOLOGI	C LOG	
See attached log		1					
					.		
	-						
							
		 					
			 				
	·	+	 				
7 CONTRACTORIS ON LANDONA PERIO CONTRACTORIS	NAL TAIL		L				
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION	N: This water well wa	s (1) constru	cted, (2) recor	nstructed, or (3) p	lugged unde	er my jurisdic	tion and was
completed on (mo/day/year) . 37-86	This 185-4 105-		and this record	a is true to the bea	st of my kno	wledge and b	elief. Kansas
under the business name of Henkle Drilling &	Supply Co 1	m Hecord Wa	s completed o	on (mo/day/yr) . 4 ure) B	,		
INSTRUCTIONS: Use typewriter or ball point pen, <u>PLEASE</u>		•	by (signati	JID) <i>F J A A</i>			- will
	PRESS FIRMLY and	PRINT clear	v. Please fill in	blanks, underline	or circle the	correct answ	ers. Send ton
three copies to Kansas Department of Health and Environme OWNER and retain one for your records.	PRESS FIRMLY and	PRINT clear	v. Please fill in	blanks, underline	or circle the	correct answ	ers. Send top /ATER WELL

DRILLERS TEST LOG

CUSTOMERS NAME	Kirby Clawson	DATE 1-22-86
STREET ADDRESS .		TEST # 1 E. LOG yes
CITY & STATE	Satanta, KS 67870	DRILLER Livingston
COUNTY Stanton	QUARTER NE SECTION_	10 TOWNSHIP 30 RANGE 40
LOCATION	1	,

	ООТА		WELL LOCATION
	በበጥል		
	FOOTAGE From Pay To		Static Water Level
From	Pay	 	DESCRIPTION OF STRATA Proposed Well Depth
0		2	Top Soil
2		140	Brown sandy clay, caliche and few fine sand stks.
140	ļ	155	Sand fine to medium, coarse
155	· 	177	Brown sandy, clay and few sand stks.
177		220	Sand fine to medium, coarse, few small gravel and clay stks
220		238	Sand fine to medium, coarse
238		250	Brown sandy clay and limerock
250	10	260	Sand fine to medium, coarse, small gravel
260	23	283	Sand fine to medium, coarse, small to medium, brown gravel,
			and few tight places
283		290	Brown sandy clay
290		300	Brown sandy clay and fine sand
300	10	310	Sand fine, small
310		316	Brown sandy clay and limerock
316		330	Soapstone, yellow
330		380	Weathered shale, hard ledge at 352'
380	10	390	Dakota and few shale stks.
390		400	Shale and limestone stks.
400	10	410	Dakota and shale stks.
410		427	Limestone, soapstone and redish clay and few Dakota stks.,
			stks, hard in places, changed bits
427		446	Red shale and limestone and scapstone and few Dakota stks.
		460	Soapstone and limestone stks.
	15	475	Dakota and soapstone
		480	Red shale and soapstone
			Dakota and soapstone, started using water at 510'
	27		Limestone and soapstone and Dakota frim
612		650	Red bed
			
			TOTAL DEPTH - 615'
			Set up - North
			Pit on the East
	155 177 220 238 250 260 283 290 300 310 316 330 380 390 400 410	140 155 177 220 238 250 10 260 23 290 300 10 316 3 330 10 340 10 390 4 400 10 410 4 446 4 475 4 480 105 585 27	140 155 155 177 177 220 220 238 238 250 250 10 260 260 23 283 283 290 290 300 300 10 310 310 316 316 330 380 10 390 390 400 400 10 410 410 427 446 446 460 460 446 475 480 480 105 585 585 27 612

GARDEN CITY, KS
Phone 276-3278
TEST HOLES * * * * * *

HENKLE DRILLING & SUPPLY CO., INC.
IRRIGATION HEADQUARTERS

SUBLETTE, KS Phone 675-4311