


1 LOCATION OF WATER WELL: County: <b>Kingman</b>		Fraction <b>SE 1/4 SW 1/4 SE 1/4</b>	Section Number <b>3</b>	Township Number <b>T 30 S</b>	Range Number <b>R 5 E W</b>
Distance and direction from nearest town or city street address of well if located within city? <b>110 W. Burns, Norwick, KS.</b>					
2 WATER WELL OWNER: <b>Kyles Service</b> RR#, St. Address, Box #: <b>110 W. Burns</b> City, State, ZIP Code: <b>Norwick, KS.</b> Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: 		4 DEPTH OF COMPLETED WELL <b>25'</b> ft. ELEVATION: Depth(s) Groundwater Encountered <b>120'</b> ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL <b>19.52</b> ft. below land surface measured on mo/day/yr <b>11-9-95</b> Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm Bore Hole Diameter <b>8 1/2"</b> in. to <b>25'</b> ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only <b>10 Monitoring well</b> Was a chemical/bacteriological sample submitted to Department? Yes No <b>X</b> If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes <b>No</b>			
5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped <b>2 PVC</b> 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <b>2.375</b> in. to <b>15'</b> ft. Dia in. to ft. Dia in. to <b>SDR 13</b> ft. Casing height above land surface <b>Flush Mt.</b> in. weight lbs./ft. Wall thickness or gauge No. <b>SCH. 40</b> TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot <b>3 Mill slot</b> 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 2 Louvered shutter 4 Key punched 6 Wire wrapped 9 Drilled holes 7 Torch cut 10 Other (specify) SCREEN-PERFORATED INTERVALS: From <b>25'</b> ft. to <b>15'</b> ft. From ft. to ft. From ft. to ft. From ft. to ft. GRAVEL PACK INTERVALS: From <b>25'</b> ft. to <b>13'</b> ft. From ft. to ft. From ft. to ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals: From <b>13'</b> ft. to <b>5'</b> ft. From <b>5'</b> ft. to <b>0'</b> ft. From ft. to ft. What is the nearest source of possible contamination: 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? <b>South</b> How many feet? <b>150'</b>					
FROM	TO	LITHOLOGIC LOG		FROM	TO
0	7	Grass-dk brn sandy clay, moist, root frag., earthy odor, low plasticity, stiff to firm.			
7	8.50	Reddish brn clayey sand, moist, no odor, fine-coarse grained.			
8.50	25'	Red brn-tan brn sand, dry, no odor, fine-coarse grained, poorly sorted, subrounded. Wet at 20', no odor.			
Flush MT. OK'd by Don Taylor					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <b>constructed</b> (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <b>11-9-95</b> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <b>539</b> This Water Well Record was completed on (mo/day/yr) <b>11-10-95</b> under the business name of <b>JB Environmental Drilling</b> by (signature) <b>James Bieber</b>					