			WATE	R WELL RECORD	Form WWC-5	KSA 82	a-1212			
LOCATIO	N OF WAT	ER WELL:	Fraction		Sect	on Number	Township Number	er Range Nu	ımber	
County:	Kingma	n	1SE 1/4	SE 14 SE	1/4 3	5	_ ⊤ კე	s R 5	EW)_	
Distance ar	nd direction	from nearest town	or city street a	ddress of well if locate	d within city?					
442	E. Bur	ns, Norwi								
WATER	WELL OW	NEM:	n Jennir	-						
RR#, St. Address, Box # : 442 E. Burns							Board of Agriculture, Division of Water Resources			
City, State, ZIP Code : Norwich, KS.							Application Number:			
LOCATE	WELL'S LC	CATION WITH 4	DEPTH OF C	OMPLETED WELL. 🛱	26.6	. ft. ELEV	ATION:			
J AN "X" I	N SECTION	BOX:	epth(s) Ground	water Encountered 1	20 '	ft.	2	ft. 3	ft.	
т Г		· N	ELL'S STATIC	WATER LEVEL . 18	61 ft. be	low land su	rface measured on mo	day/yr 7-19-94		
I							after ho			
Est. Yield gpm: Well water was ft. after hours pumping										
	-	Be	ore Hole Diame	eter 'T'S' in to	266		andft.			
* w -	- 			O BE USED AS:	5 Public water		8 Air conditioning	11 Injection well		
-	i	i '	1 Domestic	3 Feedlot			9 Dewatering	•	pelow)	
-	- SW	SE	2 Irrigation				10 Monitoring well			
	-	l lw	-				resNoX			
<u> </u>	' 		itted	sactoriological campio			ater Well Disinfected?	/ \	7.0 1.40 000	
5 TYPE O	E BLANK C	ASING USED:	ittou	5 Wrought iron	8 Concre			S: Glued Clamp	ed	
1 Ste		3 RMP (SR)		6 Asbestos-Cement		specify belo		Welded	1	
2 PV		4 ABS		7 Fiberglass	`	' '		Threaded X		
		ว. ชวี5์ััััััััััััััั้	to 16				ft., Dia		13 ft	
							/ft. Wall thickness or g		40	
•	•	R PERFORATION		, weight	7 PV	_	10 Asbesto	augo mon minimum		
1 Ste		3 Stainless s		5 Fiberglass		실 P(SR)				
			6 Concrete tile 9 ABS			11 Other (specify)				
2 Brass 4 Galvanized steel				5 Gauzed wrapped		,	8 Saw cut	11 None (ope	n hole)	
SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot				6 Wire wrapped			9 Drilled holes	11 None (ope	ii riole)	
1 Continuous slot 3 Mill slot 6 Wire wrap 2 Louvered shutter 4 Key punched 7 Torch cut										
		ED INTERVALS:	From2	6 # to	16	# Er	om	# 10		
SCHEEN-F	ENFONATE	D INTERVALS.	From	ft to			om	ft to	ft	
C	DAVEL DA	CK INTERVALS:	From 21	12' ft to	14'		om	ft to	ft	
	MAVELIA	SK INTERVALO.	From	ft. to		ft., Fr	om		ft.	
6 GBOUT	MATERIAL	: 1 Neat cer		2 Cement grout	(3) Bento		Other			
	vale: From	n 14' of	10 3' (ft From 3	t	_				
Grout Intervals: From 14 3ft. to 3 ft., From 3 5t. to 0 ft., From ft. to What is the nearest source of possible contamination:										
1 Septic tank 4 Lateral lines				- 13			Fuel storage Forger 15 Oil well/Gas well			
	2 Sewer lines 5 Cess pool			_			retilizer storage 16 Other (specify below)			
	3 Watertight sewer lines 6 Seepage pit						secticide storage			
Direction from well? (1)04\$							any feet? 5'			
FROM	TO TO		LITHOLOGIC	LOG	FROM	TO		GING INTERVALS		
0	.75	Gravel								
.75	4.25		ravelly	sandy clay,	firm.mo	ist.				
• , ,	1.25			ry coarse s			A			
4 25	26'6			, dry, no t		odor				
7.43	400	fine-coar				JUJI				
		A+ 20' 6	irau can	d, fine-ver	Vicoarse	grait	ed.			
		mod. odor		WA TIME VET	JUGITE	9141	× × 1			
		mod odor	wel.							
J	L			IONI THE		L	1			
7 CONTE	RACTOR'S (DR LANDOWNER'S	S CERTIFICAT 1				constructed, or (3) plug			
completed	on (mo/day	/year) 7-18-9				and this red	cord is true to the best of	of my knowledge and be	ellet. Kansas	
Water Wel	Contractor	s License No	539	This Water \	Well Record wa	s complete	d on (mo/day/yr) 7-a	an bar		
under the	business na	me of JB	Environm	ental Drill	ıng	by (sign	nature) Pames	JUNE		
								and the second s		