WATER WELL RECORD			Form WW	/C-5		r Resources App. N		
1 LOCATION OF WATER WELL:		Fraction		Section Number	Township No.	Range Number		
County: Kingman			SE 4 NG 4 SE	14 >6 1/4	9	T 30 S	R5 □E ☑W	
Stree	et/Rural	Address of Well Location; i	f unknown, distance & c	direction	Global Positioning			
1		town or intersection: If at o	•	Latitude: (in decimal degrees)				
1 mile west and 1 mile south of Norwich, KS					Longitude: (in decimal degrees) Elevation:			
				Datum: WGS 8	4. □ NAD 83 □	 I NAD 27		
2 WATER WELL OWNER: WAYNE VAN GIESCH					Collection Method:			
RR#, Succi Address, Box #. 12763 SE 1460 FH					GPS unit (Make/Model:)			
							c Map, Land Survey	
Nozwey Vs. 67118					Est. Accuracy:	♂m, ∐ 3-5 m, L	3-15 m, ∐>15 m	
WITH AN "X" IN 4 DEPTH OF COMPLETED WELL 4@200 ft.								
	SECTION BOX: Depth(s) Groundwater Encountered (1).? ft. (2)							
	N WELL'S STATIC WATER LEVELft. below land surface measured on mo/day/yr							
	Pump test data: Well water wasft. after hours pumping gpm							
EST. YIELDgpm. Well water wasft. after hours pumpinggpm								
W E Bore Hole Diameter 5 in. to .200 ft., and in. to ft.								
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well								
SW SE Domestic Feedlot Oil field water supply Dewatering Other (Specify below)								
☐ Irrigation ☐ Industrial ☐ Domestic-lawn & garden ☐ Monitoring well								
Was a chemical/bacteriological sample submitted to Department?								
S If yes, mo/day/yr sample was submitted								
Water went distincted:								
5 TYPE OF CASING USED: Steel PVC Other Poly.  CASING JOINTS: Glued Clamped Welded Threaded								
Casing diameter .3/4" in to .200 ft., Diameter in to ft., Diameter in to ft.								
Casing height above land surface in., Weightlbs./ft., Wall thickness or gauge No								
TYPE OF SCREEN OR PERFORATION MATERIAL:   Steel								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole)								
Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS:         From								
GRAVEL PACK INTERVALS: From								
From								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From 0 ft. to 200 ft., From ft. to ft. ft. ft.								
What is the nearest source of possible contamination:								
Septic tank								
Sewer lines Cesspool Sewage lagoon Fuel storage Abandoned water well								
Dire	watertig	South			orage			
FROM	TO	LITHOLOG	ICLOG	FROM			GGING INTERVALS	
0	20	Gravel/sand	C LOG	INOIVI	LITTO. LI	JO (WIII.) OI FLU	OURIGINIERVALS	
20	75	Sand			<del></del>	·····		
75	200	Sand-Shale						
	1===							
						Mar 1887		
						······································		
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was   ☐ constructed, ☐ reconstructed, or ☐ plugged								
under my jurisdiction and was completed on (mo/day/year) .6-12-2012 and this record is true to the best of my knowledge and belief.								
Kansas Water Well Contractor's License No. 835 This Water Well Record was completed on 1800/day/year 127/2012								
under the business name of Basqall Geothermal Drilling Inc. by (signature)  INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct answers. Send three copies								
INSTRU	CTIONS:	Use ty pewriter or ball point pen.	PLEASE PRESS FIRMLY as	nd <i>PRINT</i> clea	rly. Please fill in blanks	and check the correc	t answers. Send three copies	
Telephone	uc, pınık)t : 785–296–	o Kansas Depar tment of Health a 5524. Send one copy to WATE	ER WELL OWNER and retail	water, Geologin one for ve	gy Section, 1000 SW Jac our records. Include fee	of \$5.00 for each co	nstructed well Vi eit ne at	
		ov/waterwell/index.html.	OWILK and I Co		- records. I melude let	. OI #5.00 TOI CACII CO	went vi sit us at	
KSA 82a-1212 Check: White Copy, Blue Copy, Pink Copy								