

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: Kingman		C 1/4 SE 1/4 SW 1/4		36		T 30 S		R 7 EW	
Distance and direction from nearest town or city street address of well if located within city?									
1 south, 2 1/2 East of Rago, Ks.									
2 WATER WELL OWNER:		Duke Drilling PO Box 823 Great Bend, Ks. 67530							
RR#, St. Address, Box # :		Board of Agriculture, Division of Water Resources							
City, State, ZIP Code :		Application Number: 970020							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 95 ft. ELEVATION:							
		Depth(s) Groundwater Encountered 1. ft. 2. ft. 3. ft. WELL'S STATIC WATER LEVEL 50 ft. below land surface measured on mo/day/yr 1-24-97 Pump test data: Well water was ft. after hours pumping gpm Est. Yield na gpm Well water was ft. after hours pumping gpm Bore Hole Diameter .9 in. to .95 ft. and in. to ft. WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well Was a chemical/bacteriological sample submitted to Department? Yes No X; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes No X							
5 TYPE OF BLANK CASING USED:		CASING JOINTS: Glued X Clamped							
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile		Welded							
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below)		Threaded							
7 Fiberglass									
Blank casing diameter 5 in. to 6.5 ft. Dia in. to ft. Dia in. to ft.									
Casing height above land surface 2' in. weight SDR 26 lbs./ft. Wall thickness or gauge No.									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 95 ft. to 65 ft. From ft. to ft.									
GRAVEL PACK INTERVALS: From 95 ft. to 20 ft. From ft. to ft.									
From ft. to ft. From ft. to ft.									
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other hole plug									
Grout Intervals: From 20 ft. to 0 ft. From ft. to ft. From ft. to ft.									
What is the nearest source of possible contamination:		10 Livestock pens 14 Abandoned water well							
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage									
Direction from well? south west How many feet? 200'									
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS				
0	3	Top soil							
3	11	Brown clay							
11	25	Sandy brown clay and fine sand							
25	90	Medium sand little clay and gravel							
90	95	Sand, medium some clay.							
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-24-97 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 2-3-97 under the business name of Rosencrantz=Bemis by (signature) Fredia Dodson									
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.									