


#12

WATER WELL RECORD Form WWC-5 KSA 82a-1212

1 LOCATION OF WATER WELL:		Fraction		Section Number		Township Number		Range Number	
County: <u>Kingman</u>		NW 1/4 NW 1/4 NW 1/4		15		T 30 S		R 7 W	
Distance and direction from nearest town or city street address of well if located within city? <u>Kingman</u> 1/2 Mile south of Rago, Kansas									
2 WATER WELL OWNER:		Phillips Petroleum Co.							
RR#, St. Address, Box # :		Bartlesville, Okla. 74004							
City, State, ZIP Code :		Board of Agriculture, Division of Water Resources Application Number:							
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 27' ft. ELEVATION:							
<div style="text-align: center;">N 1 Mile W E S</div> 		Depth(s) Groundwater Encountered 1. 9' ft. 2. ft. 3. ft.							
		WELL'S STATIC WATER LEVEL 9' ft. below land surface measured on mo/day/yr <u>Mar. 9-83</u>							
		Pump test data: Well water was ft. after hours pumping gpm							
		Est. Yield gpm: Well water was ft. after hours pumping gpm							
		Bore Hole Diameter 7 7/8 in. to 27' ft., and in. to ft.							
TYPE OF BLANK CASING USED:		5 Wrought iron 8 Concrete tile CASING JOINTS: Glued <input checked="" type="checkbox"/> Clamped							
1 Steel 3 RMP (SR)		6 Asbestos-Cement 9 Other (specify below) Welded							
2 PVC <input checked="" type="checkbox"/> 4 ABS		7 Fiberglass Threaded							
Blank casing diameter 4 in. to 5 ft., Dia in. to ft., Dia in. to ft.									
Casing height above land surface 24 in., weight Schedule 40 lbs./ft. Wall thickness or gauge No. Schedule 40									
TYPE OF SCREEN OR PERFORATION MATERIAL:		7 PVC <input checked="" type="checkbox"/> 10 Asbestos-cement							
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)									
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)									
SCREEN OR PERFORATION OPENINGS ARE:		5 Gauzed wrapped 8 Saw cut <input checked="" type="checkbox"/> 11 None (open hole)							
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
SCREEN-PERFORATED INTERVALS: From 5' ft. to 27' ft., From ft. to ft.									
GRAVEL PACK INTERVALS: From 5 ft. to 27 ft., From ft. to ft.									
FROM TO LITHOLOGIC LOG		FROM TO LITHOLOGIC LOG							
0'	5'	Sandy top soil.							
5'	10'	Brown clay.							
10'	15'	Brown clay.							
15'	20'	Medium fine sand.							
20'	23'	Red clay.							
23'	27'	Medium course sand.							
		Sand bottom							
6 GROUT MATERIAL: 1 Neat cement <input checked="" type="checkbox"/> 2 Cement grout 3 Bentonite 4 Other									
Grout Intervals: From ft. to ft., From 0 ft. to 5 ft., From ft. to ft.									
What is the nearest source of possible contamination:									
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well									
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage <input checked="" type="checkbox"/> 15 Oil well/Gas well									
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)									
Direction from well? SW How many feet? 250'									
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>Mar 9-83</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. <u>112</u> This Water Well Record was completed on (mo/day/yr) <u>April 29-83</u> under the business name of <u>Wells Drilling Co.</u> by (signature) <u>Rai Wells</u>									
INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.									