

MW-21

1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: <u>Kingman</u>		<u>NW 1/4 NW 1/4 NE 1/4</u>	<u>1535</u>	T <u>30</u> S	R <u>7</u> E/W
Distance and direction from nearest town or city street address of well if located within city?					
2 WATER WELL OWNER:					
RR#, St. Address, Box # :			Board of Agriculture, Division of Water Resources		
City, State, ZIP Code :			Application Number:		
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL <u>49</u> ft. ELEVATION: <u>1938.61</u>			
		Depth(s) Groundwater Encountered 1 ft. 2 ft. 3 ft. WELL'S STATIC WATER LEVEL ft. below land surface measured on mo/day/yr Pump test data: Well water was ft. after hours pumping gpm Est. Yield gpm: Well water was ft. after hours pumping gpm WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well 1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below) 2 Irrigation 4 Industrial 7 Domestic (lawn & garden) 10 Monitoring well <u>MW 21</u>			
		Was a chemical/bacteriological sample submitted to Department? Yes No <u>X</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>(NO)</u>			
		5 TYPE OF BLANK CASING USED:			
		1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped 2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded Blank casing diameter <u>4 1/2</u> in. to <u>19</u> ft., Dia in. to ft., Dia in. to ft. Casing height above land surface <u>3</u> in., weight lbs./ft. Wall thickness or gauge No. TYPE OF SCREEN OR PERFORATION MATERIAL: 7 Fiberglass Threaded 1 Steel 3 Stainless Steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-Cement 2 Brass 4 Galvanized Steel 6 Concrete tile 9 ABS 11 Other (Specify) 12 None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole) 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ft. SCREEN-PERFORATED INTERVALS: From <u>49</u> ft. to <u>19</u> ft., From ft. to ft. GRAVEL PACK INTERVALS: From <u>49</u> ft. to <u>17</u> ft., From ft. to ft. From <u>17</u> ft. to <u>14</u> ft., From ft. to ft.			
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From <u>14</u> ft. to <u>1</u> ft., From ft. to ft., From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below) 13 Insecticide storage Direction from well? How many feet?					
FROM	TO	LITHOLOGIC LOG	FROM	TO	PLUGGING INTERVALS
0	4	clay sandy silt, rust, firm	49	19	Natural sand
4	8	most w/ trace roots rust sand, most fine grained	17	14	Secondary sand
8	12	grading tan medium	14	1	Grout
12	19	med to coarse sand with trace fine gravel			
19	49	sandy gravel			
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) <u>8-22-05</u> and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's Licence No <u>704</u> This Water Well Record was completed on (mo/day/yr) <u>8-22-05</u> under the business name of <u>MAXS</u> by (signature) <u>David H. Hays</u>					