


1 LOCATION OF WATER WELL:		Fraction	Section Number	Township Number	Range Number
County: Kingman		NE 1/4 NW 1/4 NW 1/4	15	T 30 S	R 8w E/W
Distance and direction from nearest town or city street address of well if located within city? 1 mile west of Spivey					
2 WATER WELL OWNER: Billy Backues					
RR#, St. Address, Box # : 3885 SW 110 th					
City, State, ZIP Code : Spivey, Ks. 67142					
Board of Agriculture, Division of Water Resources Application Number:					
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:		4 DEPTH OF COMPLETED WELL: 32 ft. ELEVATION:			
		Depth(s) Groundwater Encountered 1. 22 ft. 2. ft. 3. ft.			
		WELL'S STATIC WATER LEVEL 7' ft. below land surface measured on mo/day/yr 3-27-97			
		Pump test data: Well water was ft. after hours pumping gpm			
		Est. Yield 10 gpm: Well water was ft. after hours pumping gpm			
		Bore Hole Diameter 9 in. to 42 ft., and in. to ft.			
		WELL WATER TO BE USED AS:			
		1 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)			
		2 Irrigation 4 Industrial 7 Lawn and garden only 10 Monitoring well			
		Was a chemical/bacteriological sample submitted to Department? Yes <u>No</u> ; If yes, mo/day/yr sample was submitted			
		Water Well Disinfected? Yes <u>No</u>			
5 TYPE OF BLANK CASING USED:					
1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: <u>Glued</u> Clamped					
2 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded					
Blank casing diameter 5 in. to 31 ft. Dia in. to ft. Dia in. to ft.					
Casing height above land surface 18 in. weight lbs./ft. Wall thickness or gauge No. 210					
TYPE OF SCREEN OR PERFORATION MATERIAL:					
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 10 Asbestos-cement					
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 11 Other (specify)					
SCREEN OR PERFORATION OPENINGS ARE:					
5 Gauzed wrapped 8 Saw cut 11 None (open hole)					
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes					
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)					
SCREEN-PERFORATED INTERVALS: From 31 ft. to 36 ft. From ft. to ft.					
GRAVEL PACK INTERVALS: From 36 ft. to 23 ft. From ft. to ft.					
6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other					
Grout Intervals: From 3 ft. to 23 ft. From ft. to ft. From ft. to ft.					
What is the nearest source of possible contamination:					
1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well					
2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well					
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)					
13 Insecticide storage					
Direction from well? SE How many feet? 800					
LITHOLOGIC LOG					
FROM	TO			FROM	TO
0	12	sandy soil			
12	22	sand some coarse			
22	26	sand			
26	32	shale			
PLUGGING INTERVALS					
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) <u>constructed</u> , (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 3-27-97 and this record is true to the best of my knowledge and belief. Kansas					
Water Well Contractor's License No. 140 This Water Well Record was completed on (mo/day/yr) 4-12-97					
under the business name of Lyman Inc. by (signature) <i>Lyman Inc.</i>					
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Topeka, Kansas 66620-0001. Telephone: 913-296-5545. Send one to WATER WELL OWNER and retain one for your records.					