				IER WELL	HECORD	Form W	VC-5 KSA	82a-1212			
	ON OF WAT		Fraction				Section Num		ip Number	Range	Number
	Kingman		$C/W_{\frac{1}{2}}$		1/4	SE 1/4		т 3	U S	R 😕	¥ω
Distance a	and direction	from nearest town	or city stree	t address o	f well if loca	ated within o	ity?				
$3\frac{1}{2}$ S	outh, $\frac{1}{2}$	east of Ze	nda,Ks.								
	R WELL OW	· ·		Resour	ces Co	rp.					
	Address, Box					-	rive #225	Board	of Agriculture,	Division of Wa	ter Resources
l '	, ZIP Code				kas 770			Applic			
		OCATION WITH									
AN "X"	IN SECTION	OCATION WITH 4 N BOX:	J								1
_		<u> </u>						ft. 2			T I
Ī	! !	! [V						surface measure	, ,		1
	NW	NE						ft. after			
	1	E	Est. Yield	gp	m: Well w	ater was .		ft. after	hours pu	ımping	gpm
<u>.</u>	i		Bore Hole Dia	meter	in. [.]	to		ft., and	ir	. to	
W	1	! ~ ¾	VELL WATE	R TO BE U	SED AS:	5 Public	water supply	8 Air condition	ning 11	Injection well	9
-	- 1	i ^{	1 Domes	tic 3	Feedlot	6 Oil fiel	d water supply		12	•	1 '
-	SW	SE	2 Irrigation		Industrial			ly 10 Monitoring			
	!	!	Ū				•	? YesNo			1.3
∮ ∟				ai/Dacterioic	yicai sampi	e submitted	to Department			• •	
-r			nitted					Water Well Disint		No	mped
μ .		CASING USED:			ught iron		oncrete tile		JOINTS: Glue		1
1 Ste	eel	3 RMP (SR)	1	6 Asbe	estos-Cemer	nt 9 O	ther (specify b	elow)		led	1
2 PV	/C	4 ABS		7 Fiber	rglass	Λ	\.		Thre	aded	
Blank casi	ng diameter	ir	n. to	ft.	., Dia		n]tb[ft., Dia		in. to \dots .	ft.
Casing he	ight above la	and surface		in., wei	ght	/\	X.	lbs./ft. Wall thickn	ess or gauge N	lo	
		R PERFORATION			-	1/23 5 d	7 PVC		Asbestos-cem		
1 Ste	eel	3 Stainless	steel	5 Fiber	rglass	~ ~	RMP (SR)		Other (specify		
2 Br		4 Galvanize			crete tile	*	ABS		None used (or		
		RATION OPENING		o doug	# <i>9</i> 1	uzed wrapp		8 Saw cut	THORIC USCU (O)	•	non holo)
			-	/	110 / 1		eu		1	11 None (o	Jen noie)
1	ontinuous slo			Λ		e wrapped		9 Drilled ho			
2 Louvered shutter 4 Key punched / V 7 Torch cut 10 Other (specify)											
SCREEN-I	PERFORATE	ED INTERVALS:		1 /							
			From		ft. to			From	ft.	to	ft. _
(GRAVEL PA	CK INTERVALS:	From		ft. to		ft.,	From	ft.	to	
			From		ft. to		ft.,	From	ft.	to	ft.
6 GROUT	Γ MATERIAL	: 1 Neat ce	ment	2 Ceme	nt grout		Bentonite				
Grout Inter		m			-						i i
1		ource of possible of						ivestock pens		bandoned wa	
	eptic tank	4 Lateral			7 Dit priva			uel storage		Dil well/Gas we	1
	•				7 Pit privy			-			Í
	ewer lines	5 Cess p			8 Sewage I	agoon		ertilizer storage		Other (specify I	below)
i	•	er lines 6 Seepa	ge pit	,	9 Feedyard			nsecticide storage			
Direction f								many feet?	5111001110		
FROM	то		LITHOLOG	IC LOG		FRO	M TO		PLUGGING	INTERVALS	
0	3	Top soil									· · · · · · · · · · · · · · · · · · ·
3	6	Brown cl						no casi	ng set,pl	ug with s	sand and
6	15	Dirty sa						grave!	95' to 20	', hole r	olug
15	30	Gray & w		av cali	che				ground le		
30	34	Brown cl	av		~~~						
1			-								
34	48	Brown &	gray Cla	<u>ay</u>							
48	51	Sand and	<u>gravel</u>								
51	55	Sandy cl						+			
55	60	Redish k									
60	75	Brown &									
75	85	Tough br	own & g	ray cla	У						
85	90	Redish k	prown cla	ay							
90	95	Red bed.			,						
		, wa wa				1					
											1 i
—	L						L	-			
		OR LANDOWNER'S									
		year) 3-1								owledge and	pelief. Kansas
		s License No								7/ 	
under the business name of Rosencrantz-Bemis by (signature) Fredia Wedson											
INSTRU	CTIONS: Use tv	pewriter or ball point pe				Please fill in bl			ers. Send ton three	copies to Kansas	Department
1 "*******		point pe	10- 111-0	unu	J.ourity.				co top times	· · · · · · · · · · · · · · · · ·	- >====================================