


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		County Kingman	Fraction ne SW sw 1/4 1/4 1/4	Section number 22	Township number X 30 T S R	Range number 9 E/W
2. Distance and direction from nearest town or city: 1w 1 1/2 s Zenda			3. Owner of well: Kenton Swingle R.R. or street: City, state, zip code: Zenda, Ks			
4. Locate with "X" in section below: N W E S 1 Mile			Sketch map: 			
5. Type and color of material			From	To	6. Bore hole dia. 8 in. Completion date Well depth 72 ft. 7-24-79	
soil and fine sand			0	9	7. <input checked="" type="checkbox"/> Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
clay			9	11	8. Use: <input checked="" type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other	
medium sand			11	20	9. Casing: Material <input type="checkbox"/> Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 15 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 282 lbs./ft. Dia. 5 in. to 72 ft. depth Wall Thickness 258 inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gauge No. 258	
clay			20	32	10. Screen: Manufacturer's name Pumpco Type pvc Dia. 5 Slot/gauze 025 Length 16 Set between 62 ft. and 72 ft. ft. and <input type="checkbox"/> ft. Gravel pack? <input checked="" type="checkbox"/> Size range of material 1/2 in	
sandy clay			32	35	11. Static water level: 14 ft. below land surface Date 6-30-79 mg./day/yr.	
silty sand			35	41	12. Pumping level below land surfaces: ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. ft. after <input type="checkbox"/> hrs. pumping <input type="checkbox"/> g.p.m. Estimated maximum yield 50 g.p.m.	
clay			41	43	13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date	
sand w/ clay lenses			43	49	14. Well head completion: <input checked="" type="checkbox"/> Pitless adapter 15 Inches above grade	
fine sand			49	55	15. Well grouted? <input checked="" type="checkbox"/> With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 3 ft. to 15 ft.	
sand w/ clay			55	59	16. Nearest source of possible contamination: ft. 200 Direction E Type POND Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
medium sand			59	71	17. Pump: <input type="checkbox"/> Not installed Manufacturer's name I cuzzi Model number 5S4B HP 1/2 Volts 230 Length of drop pipe 42 ft. capacity 15 g.p.m. Type: <input checked="" type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
shale			71	72	20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Lyman Bros. 140 Business name License No. Address MI Signed W.H. Lyman Date 8-25-79 Authorized representative	
18. Elevation:			19. Remarks: Customer to pour slab			
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley						