		WA	TER WELL REC	ORD Form W\	NC-5 KS	4 82a-1212	: ID No	o			
		ER WELL:	Fraction	67° 7	T-1	Section		Township No	[Range Num	
County: Kir			NW 1/4	74 -	JE ¼	10		т 30	S	R 9w	E/W
		rom nearest tow	vn or city street a	ddress of well if lo	cated within	city?					
	a, Ks.	IED. Towers	Tille d Amore		Chowlin	v Dwill	ing Co	7777 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7 7	Mort +mor	A 4-10	
_		IER: Larry			Sterlin	-	_	anpany .	MITT THE	A 4-10	
RR#, St. Addro City, State, ZIF	P Code	: Zenda	SW 90th , KS 67159)	P. O. Bo	Ks. 671	.24	Application	Number: 29	sion of Water Ro	
3 LOCATE W	ELL'S LO	CATION WITH	4 DEPTH OF C	OMPLETED WEL	L 104	f	t. ELEVA	rion:unknow	m		
AN "X" IN S			Depth(s) Groun	dwater Encounter	ed 1	50	ft.	2e measured on mo	ft. 3		ft.
			Pur	np test data: We	l water was .		ft. a	after	hours pur	ping	gpm
	w	- NF						ıfter			gpm
'`	w X	1	1 Domestic	TO BE USED AS: 3 Feedlot		water suppl I water sup	•	8 Air conditioning9 Dewatering	,	ction well er (Specify belov	w)
w	1	— <u>⊹</u> — ∈	2 Irrigation	4 Industrial				10 Monitoring well			
"	<u>'</u>		J			`	,	·			
s	w -	- SE	Was a chemica	l/bacteriological sa	ample submit	ed to Depa	artment? Y	es No	· If ves. mo/	day/vrs sample	was sub-
	1	1	mitted	arbaotoriological co	impio odbinii	od to Bope		ater Well Disinfecte		No	
	<u> </u>										
5 TYPE OF	BLANKC	ASING USED:		5 Wrought iron	R	Concrete til	اما	CASING IO	NTS: Glued	Clamped	!
1 Steel	DLAINI O	3 RMP (SF	₹)	6 Asbestos-Cem	Other (spec			NG JOINTS: Glued Clamped			
2 PVC		4 ABS	•	7 Fiberglass						ed	
								ft., Dia			
Casing height	above lar	nd surface	12	in., weight	2.8			lbs./ft. Wall thickne	ss or guage	NoS ch. 40	J
TYPE OF SCI	REEN OR	PERFORATIO				7 PVC			estos-Cemer		
1 Steel		 Stainless Galvaniz 		5 Fiberglass 6 Concrete tile	8 RMP (S 9 ABS	SR)		ther (Specify)one used (open hole)			
2 Brass									٠.	,	
SCREEN OR		5 Guazed wrapped6 Wire wrapped			8 Saw cut 11 None (open hole) 9 Drilled holes			iole)			
1 Continu 2 Louvere			ill slot ey punched		Torch cut	au .		10 Other (specify	·)		ft.
1		D INTERVALS:	, ,	64 #	104		# Erom		•		
SCHEEN-PER	AFUNATE	D INTERVALS.			to		ft., From		ft. to		
GR	AVEL PAC	K INTERVALS:	From	.23ft.	to 104		ft., From		ft. to		ft.
			From	ft.	to		ft., From		ft. to		ft.
6 GROUT	MATERIAI	· 1 Neat	cement	2 Cement gro	ııt	3 Bentonite	<u> </u>	1 Other			
								ft., From			
		rce of possible					10 Livestock pens		14 Abandoned water well		
1 Septic	tank	4 Later	al lines	7 Pit privy			11 Fuel storage		15 Oil well/Gas well		
2 Sewer lines 5 Cess pool				8 Sewage lagoon		•		•	16 Other (specify below)		
3 Watertight sewer lines 6 Seepage pit			9 Fe		13 Insecticide storage						
Direction from	well?	South			How many feet? 100						
FROM	TO		LITHOLOGIC	LOG	FR	ОМ	го	PLU	IGGING INTE	RVALS	
0	2	top soil									
2	19	sand and	gravel								
19	24	clay									
24	104	sand and	l gravel w	ith clay st	reaks						
		shale bo	ttom								
-											
7 CONTRAC											
								enstructed, or (3) p			
								cord is true to the be d on (mo/day/yr)			
1				ell Service							
		verry.	s water we	err gerarce	, IIIC.		~, (Λ	sum,	Lood	

INSTRUCTIONS: Use typewriter or ball point pen. <u>PLEASE PRESS FIRMLY</u> and <u>PRINT</u> clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5522. Send one to WATER WELL OWNER and retain one for your records. Fee of \$5.00 for each <u>constructed</u> well.