USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number		Township number	Range number	*	
1. Location of well:	Barber	SE 1/4 SW 1/4 NE			3	1 31 s	R 10W	E.	
2. Distance and direction from nearest town or city: 5S 1 3/4 E 1/2N 3. Owner of well: Kent Lawrence									
Street address of well location if in city:									
4. Locate with "X" in section below: Sketch map:					6. Bore hole dia. 28 in. Completion date Well depth 157 ft. 15July76				
4. Locate with "X" in section below: Sketch map: NOTIFIE RANSES Sketch map: WELL STATE A. Locate with "X" in section below: Sketch map: WELL STATE Masny III e Ranses Well Masny III e Ranses Well Masny III e Ranses Notice The Masny II						7 Cable tool Rotary Driven Dug Hollow rod Jetted Bored X Reverse rotary			
						8. Use:Domestic Public supply Industry XIrrigation Air conditioning Stock Lawn Oil field water Other 9. Casing: Material St Heights Above or below			
						Threaded Welded X Surface 12 in. RMP PVC Weight 3/. 7 lbs./ft. Dia. 16n. to 106t. depth Wall Thickness: inches as			
5. Type and color of material				From	То		in lande i to:	188_	
Soil				0	2	10. Screen: Manufacturer's name W.A. Brown And Cook Type Freeflo Dia. 16"			
Sand, silty				2	23	Slot gauze 1/8" Length 50			
Sand.fine to coarse				23	59	126-136Cook and 136-156 Freefl Gravel pack? X Size range of material XX1/8			
Clay, tan Hard				59	74	11. Static water level:	mo.	/day/yr.	
Sand, fine to coarse				74	107	12. Pumping level below land	surfaces:		
Clay, tan Hard				107	110	000			
Sand, fine to coarse and medium gravel				110	136	Estimated maximum yield	900 mo.	_g.p.m. /day/yr.	
Clay, tan Hard				136	140	Yes X No	Date		
Sand, fine to coarse				140	156	Well head completion: Pitless adapter	12 Inches above	grade	
Shale, red				156	158	With: Near cement AL		Concrete -	
						Depth: From ft. to	. ra	rm -	
						Well disinfected upon comple	tion? X Yes	No	
						400-1	Not installed	~i_	
						Model number 10001 Length of drop pipe 120	HP <u> 60</u> _ Volt 2 ft. capacity <u>50</u> 0	·—·	
						Type: Submersible	_X Turbine		
(Use a second sheet if needed)						Jet Centrifugal	Recipro	cating	
18. Elevation:	19. Remarks: 20. Water well contractor's certification:							M	
	A 5'x12'x1' concrete pump and engine base was poured at surface.						This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Lentral W							& Pump	325 S	
Slope X Upland Valley Address 121 S. Taylor Authorized representative Date 2									
	us and nink conies to the Denortheau	fu_bl							