## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction	Section	number	Township number	Range number		
1. Location of well:	COMANCHE	NE 1/4 SW1/4 SW1/4	ž	21	T 31 s	18W	E/W	
2. Distance and direction from nearest town or city: 2 # \$ 3 N of R.R. or street:								
Street address of well location if in city: Coldy vature . Up 5 City, state, zip code: City, state, zip code:								
4. Locate with "X" in section below: Sketch map:					6. Bore hole dia. 30 in. Completion date			
T N					7 Cable tool Rotary Driven Dug			
draina					Hollow rod Jetted Bored 🗶 Reverse rotary			
				-	8. Use: Domestic Public supply Industry  X Irrigation Air conditioning Stock			
					Lawn Oil field water Other			
					9. Casing: Material The Height (Apove) or below Threaded Welded Surface / Z in.			
S I Mile					RMPPVCWeightlbs./ft. Dia 16 in. to 190 ft. depth Wall Thickness: inches or			
5. Type and color of material				То	Dia in. to ft. dep	oth gage No		
					10. Screen: Manufacturer's	pame		
Silt, sandy			0	2	Type	Dia		
Sand, fine to coarse with tan and white clay stks				87	Set betweenft.	_ft. and310	ft.	
Sand, fine to coarse and fine to coarse gravel				105	Gravel pack? Size ro	1.4	<u>/</u>	
Clay, white and tan			105	142	11. Static water level:  106 ft. below land su		/day/yr. <b>77</b>	
Sand, fine to coarse and fine to med. gravel				164	12. Pumping level below lan	d surfaces:		
Clay, tan				185	161 ft. after	hrs. pumping 1200	g.p.m.	
Sand, very fine to med.				196	Estimated maximum yield — 13. Water sample submitted:		g.p.m. day/yr.	
Sand, very fine to coarse and fine to med. gravel				205	Yes X No	Date		
Sand, very fine to coarse and some fine gravel				211		1 Inches above gr	rade	
					15. Well grouted? X	Bentonite Co	oncrete	
Sand, fine to coarse and fine to med. gravel				248	Depth: From ft. to			
Clay, red, sandy				250	16. Nearest source of possible ft Direction	e contamination: Type <b>130</b> 1	Ja	
Sand, fine to coarse and fine to coarse gravel				265	Well disinfected upon completely 17. Pump:		No	
Clay, tan, sandy			265	268	Manufacturer's name	Not installed	"	
Sand, very fine to coarse with some clay streaks			268	300	Model numberLength of drop pipe	HP <u>\$€</u> Volts ≥ ft. capacity <b>\$€</b> © g		
Sand, very fine to med. with some clay streaks			300	310	Type: Submersible	X_ Turbine		
Shale	(Use a second sh	eet if needed)	310	315	Jet Centrifugal	Reciproc	ating S	
18. Elevation:	19. Remarks:				20. Water well contractor's	certification:		
	6'X1Z'X8'	" Slot poured			This well was drilled under m is true to the best of my know		·   .	
Topography:	at	" Slot poured Surface		ļ	Central Well & Business name	Pump Svc. 3	325 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \	
Slope	$\omega$	Sugace			404 0 0	ylor Pratt,	] =   = 2	
Upland Valley					Signed Authorized rep	presentative 29 de	78 =	