WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

| | County | Fraction | | Section number | | Township number | Range number | |
|---|------------------|-----------------|-----|----------------|-------------------------|---|--|-------------|
| 1. Location of well: | Comanche | NW 1/4 1/4 | 1/4 | . 3 | 5 | т 31 s | r 18 x /w | |
| 2. Distance and direction from nearest town or city: 3 Miles East & I miles North, Street address of well location if in city: of Coldwater City, sto | | | | | | Mrs. Lee Turner Coldwater, Kansas | | |
| 4. Locate with "X" | | Sketch map: | | | | 6. Bore hole dia. 30 in. Well depth 266 ft. | | |
| * | NE | Well No. 4 | | | | 7 Cable tool Rotary Hollow rod Jetted | Driven Dug Bored X Reverse rotary | |
| Wile | E E | | | | | 8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other | | |
| SW SE | | | | | | 9. Casing: Material St 1 Height: Above or below Threaded Welded _X | | |
| S 1 M | | | | | | Dia 16 in. to 178ft. dept | h Wall Thickness: inches or | |
| 5. Type and color of | material | | | From | То | Dia in. to ft. dept 10. Screen: Manufacturer's no | - | |
| Sandy so: | il | | | | 1_ | Metal Product | S Dia. 16" | |
| Fine sand | | | | 1 | 15 | Slot/gauze 1/8" | Length <u>88 '</u> ft. and <u>2 66 ft.</u> | |
| Fine to | coarse sand | | | 15 | 80 | Gravel pack? Yesize ran | | |
| Clay | | | | 80 | 100 | 11. Static water level: ft. below land surf | mo./day/yr. face Date <u>5/19/76</u> | |
| Fine to coarse sand & med. gravel | | | | 100 | 127 | 12. Pumping level below land | surfaces: | |
| Clay | | | | 127 | 159 | fafa L | | • |
| Med. to coarse sand & gravel | | | | 159 | 170 | 13. Water sample submitted: | mo./day/уг. | |
| Sandy cla | ay | | | 170 | 181 | 14. Well head completion: | | |
| Fine to | coarse sand w/so | ome clay | | 181 | 215 | 15. Well grouted? | 12 Inches above grade | 4 |
| Sandy clay | | | | 215 | 223 | With: Neat cement Depth: From ft. to _ | Bentonite Concrete | _ T |
| Fine sand | | | | 223 | 229 | 16. Necrest source of possible ft. 4000 Direction | contamination: | 1 |
| Fine to coarse sand & fine gravel | | | | 229 | 265 | Well disinfected upon complete | tion? Yes K No | 1 |
| w/so | ome clay | | | | | 17. Pump: Manufacturer's name 444 Model number 27148W | ne | " [~ |
| Red shale | | | 265 | 270 | Length of drop pipe 180 | | (§)′ | |
| | | | | | | Type: Submersible | Turbine | h. |
| | (Use a second s | neet if needed) | | | | Jet Centrifugal | Reciprocating | » NY |
| 18. Elevation: | 19. Remarks: | | | | | 20. Water well contractor's co This well was drilled under my | | ١ |
| Topography: | | | | | | is true to the best of my knowl Layne Wester | 1.5 | څاځ |
| Hill Slope | | | | | | Business name Address | License No. |) ≩ |
| Upland Valley | | | | | | Signed Authorized repr | esentative Date / ZZ/ | <u>`</u> |