

WATER WELL RECORD

Form WWC-5

Division of Water Resources; App. No.

1 LOCATION OF WATER WELL: County: Comanche Fraction NE 1/4 NW 1/4 NE 1/4 Section Number 36 Township Number T 31 S Range Number R 19 EW

Distance and direction from nearest town or city street address of well if located within city? 3 miles N of Caldwell west South Ind.

2 WATER WELL OWNER: Bruce Ford RR#, St. Address, Box # 400 N. New York St. City, State, ZIP Code Coldwater, KS

3 LOCATE WELL'S LOCATION WITH AN 'X' IN SECTION BOX: [Grid with X in NE] 4 DEPTH OF COMPLETED WELL 115 ft. WELL'S STATIC WATER LEVEL 71 ft. below land surface measured on mo/day/yr 2-21-08

5 TYPE OF CASING USED: 1 Steel, 2 PVC, 3 RMP (SR), 4 ABS, 5 Wrought Iron, 6 Asbestos-Cement, 7 Fiberglass, 8 Concrete tile, 9 Other (specify below), 10 Asbestos-Cement, 11 Injection well, 12 Other (Specify below)

Blank casing diameter 5 in. to 115 ft., Diameter. 16 in. to 100 lbs./ft. Wall thickness or gauge No.

TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel, 2 Brass, 3 Stainless Steel, 4 Galvanized Steel, 5 Fiberglass, 6 Concrete tile, 7 PVC, 8 RM (SR), 9 ABS, 10 Asbestos-Cement, 11 Other (Specify), 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 1 Continuous slot, 2 Louvered shutter, 3 Mill slot, 4 Key punched, 5 Gauzed wrapped, 6 Wire wrapped, 7 Torch cut, 8 Saw Cut, 9 Drilled holes, 10 Other (specify), 11 None (open hole)

SCREEN-PERFORATED INTERVALS: From 115 ft. to 95 ft., From ... ft. to ... ft.

GRAVEL PACK INTERVALS: From 115 ft. to 22 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement, 2 Cement grout, 3 Bentonite, 4 Other. Grout Intervals: From 22 ft. to 0 ft., From ... ft. to ... ft.

What is the nearest source of possible contamination: 1 Septic tank, 2 Sewer lines, 3 Watertight sewer lines, 4 Lateral lines, 5 Cess pool, 6 Seepage pit, 7 Pit privy, 8 Sewage lagoon, 9 Feedyard, 10 Livestock pens, 11 Fuel storage, 12 Fertilizer Storage, 13 Insecticide Storage, 14 Abandoned water well, 15 Oil well/gas well, 16 Other (specify below) Nothing on location

Table with columns: FROM, TO, LITHOLOGIC LOG, FROM, TO, PLUGGING INTERVALS. Rows include: Sandy Topsoil (0-5), White Clay (5-21), Tan Clay (21-38), Fine Sand / Tan (38-68), Tan Clay (68-80), Coarse Sand (80-115)

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 2-16-08 and this record is true to the best of my knowledge and belief.

INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson St., Suite 420, Topeka, Kansas 66612-1367.