WATER	WELL RECORD F	orm WW	√C-5 K	SA 82a-12	12		
1 LOCATION OF WATER WELL: FRACTION			<b>I</b>		IP NUMBER		
	4 NW 1/4 SW	1/4	34	T 3	<u>81</u> s	R 2W	V E/W
Distance and direction from nearest town or city street address of 404 E. Spring	Conway Springs,	Kansas					
2 WATER WELL OWNER: JONES, Annie	Conway opinigs,	144113413					
RR#,ST. ADDRESS,BOX #: 404 E. Spring					Board of Agri	iculture, Division of W	Vater Resource
CITY, STATE: Conway Spring	·		P CODE:		Application Nun	nber:	
3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:	MPLETED WELL: 65	ft.		ELEVATION:			
N Depth of groundwa		ft.			ft.		ft.
WELL'S STATIC			W LAND SU		URED ON mo/o	• •	:/10
	Pump test data: Well wat			ft. after ft. after		of pumping @	gpm
Est. Yield:  Bore Hole Diame	gpm Well wat ter 12 in.	erwas to <b>6</b>	5 ft.		in.	s of pumping @ to	gpm ft.
WELL WATER TO	BE USED AS:	-			0 Newsteri		ction well
Sw - SE - 1. Domestic				ind garden on		12. Other (Sp	pecify below)
2. Irrigation	4. Industrial 6. Oil field was cteriological sample submitted to D		8. Aircon YES	ditioning	10. Monitorir	<b>ng well</b> w <u>hat</u> mo/day/yr w	vas sample
S Was a chemical/ba submitted	cteriological sample submitted to b	epartments		Vater Well Disir		_	NO
5 TYPE OF CASING USED: 5. Wrou	aht Iron 7. Fiberglass	9. Q1	ther (Specify	below) CA	SING JOINTS: (	Glued	Threaded
1. Steel 3. RPM (SR)	stos-Cement 8. Concrete til	sDI	R-26			Welded	Clamped
4. AB3	25 ft., Dia.		40	ft.,	Dia.	in to	4
12	•	in. 2 35	to			in. to	ft.
Casing height above land surface: 12 in.  TYPE OF SCREEN OR PERFORATION MATERIAL:	Weight:	2.35 It	os. / ft.	wali t	hickness or gaug	ge No214	
1. Steel 3. Stainless Steel 5. Fiberglass 7. PVC 9. ABS 11. Other (specify)							
2. Brass 4. Galvanized 6. Concret	e Tile 8. RMP (SR)	10. A	sbestos-Cer	nent 12. N	lone used (open	hole)	
SCREEN OR PERFORATION OPENINGS ARE:							
1. Continuous slot 3. Mill slot	5. Gauzed wrapped	7. <b>To</b>	rch cut	9. Dri	lled holes	11. None ( c	pen hole)
2. Louvered shutter 4. Key punched	6. Wire wrapped	8. <b>Sa</b>	w cut	10. Otl	ner (specify)		
SCREEN - PERFORATION INTERVAL From	25 ft. to	65	ft.,	From	ft.	to	ft.
From	ft. to		ft.,	From	ft.	to	ft.
GRAVEL PACK INTERVALS: From	25 ft. to	65	ft.,	From	ft.	to	ft.
From	ft. to		ft.,	From	ft.	to	ft.
6 GROUT MATERIALS: 1. Neat cement	2. Cement Grout	3	B. Bentonite		Other bent	onite hole plu	ug
						ft.	
What is the nearest source of possible contamination:  1. Septic tank  4. Lateral lines  7. Pit privy  10.			k pens	13. insec	ticide storage	15. Oil well/G	as well
The second secon					16. Other (sp	ecify below)	
Watertight sewer line     6. Seepage pit	9. Feed yard 1	2. Fertilize	r storage				
Direction from well? North				How m	nany feet? 10 f		
From To LITHOLOG	SIC LOG	From	То		LITHOLO	OGIC LOG	
0 1 topsoil							<del> </del>
1 65 shale							<u> </u>
		-					
			<del>                                     </del>				
		ļ	<u> </u>				
		<u> </u>	I				
7 Contractor's or Landowner's Certification: This wa		) 2. re	constructed	i or 3.	plugged	under my jurisdict	ion and
was completed on (mo/day/year) 6/22/20	and this record i	s true to the	e best of my	knowledge and	belief.		
Kansas Water Well Contractor's License No. 236	This water we	ell record wa	s completed	l on (mo/day/ye	ear) 6/2	25/10	
under the business name of Harp Well and P	ump Service	by (si	gnature)	Τ	odd S	. Harp	)