

1 LOCATION OF WATER WELL: Fraction NE 1/4 NW 1/4 SW 1/4 Section Number 19 Township Number T 31 S Range Number R 21 EW
 County: Clark Distance and direction from nearest town or city street address of well if located within city?

10 1/2 north of Sitka

2 WATER WELL OWNER: Sea Cat Feed Yard % Robert Seacat RR# , St. Address, Box # : RR. Ashland, Ks 67831 Board of Agriculture, Division of Water Resources City, State, ZIP Code : Bucklin, Ks. 67834 Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX: [Diagram of a 2-mile by 2-mile section box with NW, NE, SW, SE quadrants. An 'X' is marked in the SW quadrant.]
 4 DEPTH OF COMPLETED WELL: 8.0 ft. ELEVATION: ...
 Depth(s) Groundwater Encountered 1. ... ft. 2. ... ft. 3. ... ft.
 WELL'S STATIC WATER LEVEL 28.5 ft. below land surface measured on mo/day/yr 2-12-82 by Ubel
 Pump test data: Well water was ... ft. after ... hours pumping ... gpm
 Est. Yield NA gpm: Well water was ... ft. after ... hours pumping ... gpm
 Bore Hole Diameter: .24 in. to .80 in. and ... in. to ... ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 1 Domestic (3) Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? (Yes) No...x...; If yes, mo/day/yr sample was submitted by Ubel 2-2-82 Water Well Disinfected? Yes HTH No

5 TYPE OF BLANK CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued ... Clamped ...
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded .x...
 2 PVC 4 ABS 7 Fiberglass Threaded...
 Blank casing diameter 1.6 in. to 4.0 ft., Dia. ... in. to ... ft., Dia. ... in. to ... ft.
 Casing height above land surface 1.8 in., weight ... lbs./ft. Wall thickness or gauge No. 7
 TYPE OF SCREEN OR PERFORATION MATERIAL: 7 PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify) ...
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 8 Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify) ...
 SCREEN-PERFORATED INTERVALS: From 4.0 ft. to 8.0 ft., From ... ft. to ... ft.
 GRAVEL PACK INTERVALS: From 1.0 ft. to 8.0 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other ...
 Grout intervals: From 0 ft. to 1.0 ft., From ... ft. to ... ft., From ... ft. to ... ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage ...
 Direction from well? South west How many feet? 1300

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Soil			
3	12	Clay			
12	30	Sandy Clay			
30	40	Sand 20% Clay			
40	60	Clay			
60	77	Med-Fine-Coarse Sand and gravel			
77	99	Red Silty Shale			

by telephone with Don Ubel by DNB
 Log given to Ubel by Hattie

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) 1-8-81 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 134 This Water Well Record was completed on (mo/day/yr) 3-19-82 under the business name of Rosencrantz-Bemis Ent. by (signature) Nora Dodson

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
 T
 R
 21
 SEC.
 19
 NE 1/4 NW 1/4 SW 1/4