


1 LOCATION OF WATER WELL: County: Meade Fraction: SW 1/4 SW 1/4 NE 1/4 Section Number: 26 Township Number: T 31 S Range Number: R 26 E W

Distance and direction from nearest town or city street address of well if located within city?

From Fowler 3 South, 4 1/2 East, 1/4 South

2 WATER WELL OWNER: Dewayne Marsh RR#, St. Address, Box #: San City Mo 67143 Board of Agriculture, Division of Water Resources Application Number:

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 180 ft. ELEVATION:

Depth(s) Groundwater Encountered 1. 128 ft. 2. 128 ft. 3. 128 ft.
 WELL'S STATIC WATER LEVEL 128 ft. below land surface measured on mo/day/yr 9-12-83
 Pump test data: Well water was 128 ft. after 1 1/2 hours pumping 15 gpm
 Est. Yield 25 gpm; Well water was 128 ft. after 1 1/2 hours pumping 15 gpm
 Bore Hole Diameter 8 3/8 in. to 180 ft., and 180 in. to 180 ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted
 Water Well Disinfected? Yes No

5 TYPE OF BLANK CASING USED: 1 Steel 3 RMP (SR) 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued Clamped
 PVC 4 ABS 6 Asbestos-Cement 9 Other (specify below) Welded
 7 Fiberglass Threaded

Blank casing diameter 5 in. to 160 ft., Dia. 160 in. to 160 ft., Dia. 160 in. to 160 ft., Dia. 160 in. to 160 ft.
 Casing height above land surface 24 in., weight 200 lbs./ft. Wall thickness or gauge No. 40 sch

TYPE OF SCREEN OR PERFORATION MATERIAL: PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)

SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)

SCREEN-PERFORATED INTERVALS: From 160 ft. to 180 ft., From 160 ft. to 180 ft., From 160 ft. to 180 ft., From 160 ft. to 180 ft.
 GRAVEL PACK INTERVALS: From 12 ft. to 180 ft., From 12 ft. to 180 ft., From 12 ft. to 180 ft., From 12 ft. to 180 ft.

6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From top ft. to 12 ft., From 12 ft. to 180 ft., From 12 ft. to 180 ft., From 12 ft. to 180 ft.

What is the nearest source of possible contamination: none
 1 Septic tank 4 Lateral lines 7 Pit privy 10 Livestock pens 14 Abandoned water well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 11 Fuel storage 15 Oil well/Gas well
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 12 Fertilizer storage 16 Other (specify below)
 13 Insecticide storage

Direction from well? How many feet?

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	5	0/ Topsoil			
6	25	05 sand			
25	38	01 brown clay			
38	150	23 sand rock			
150	175	17 sand + gravel			
175	180	19 shale			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo/day/year) 9-12-83 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 101A This Water Well Record was completed on (mo/day/yr) 9-30-83 under the business name of Bartel Dry by (signature) Rick R Bartel

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

OFFICE USE ONLY
T
3
R
26
EWD
SEC.
26
SW 1/4
SW 1/4
NE 1/4

DD