WATER WELL RECORD		Form WWC-5		Division of Water Resources App. No.				
1 LOCATION OF WAT		Fraction		Section		Township No.		
County:		1/4 SW 1/4 Sa) 1/4 NW 1/4				R 26 □E □(W)	
Street/Rural Address of						System (GPS) in		
from nearest town or intersection: If at owner's address, check here .							(in decimal degrees)	
11036 26 Rd.							(in decimal degrees)	
Fowler, Ks. 67844				Eleva	tion:	 1	 NAD 27	
Fowler, Ks. 67844 2 WATER WELL OWNER: Kevin Hage man					Datum: WGS 84, NAD 83, NAD 27 Collection Method:			
RR#, Street Address, Box #: 1108 Box 6				GPS unit (Make/Model:)				
RR#, Street Address, Box #: City, State, ZIP Code: HCR Box 6				☐ Digital Map/Photo, ☐ Topographic Map, ☐ Land Survey				
	<u>Foulle</u>	r, Ks. 6784	<u> </u>	Est. A	ccuracy: \[<	3 m, 3-5 m, 3	5-15 m, □ >15 m	
3 LOCATE WELL WITH AN "X" IN	DEPTH OF C	COMPLETED WEL	r 32	25	ft			
						ft (3) ft	
A 500 STANDERS (100 STANDS A 100 STANDS A 10	Depth(s) Groundwater Encountered (1)							
Pump test data: Well water wasft. after hours pumping								
EST. YIELDgpm. Well water wasft. after hours pumping							ping gpm	
W							ft.	
WELL WATER TO BE USED AS: Public water supply Geothermal Injection well							njection well	
SWSE Domestic								
Irrigation Industrial Domestic-lawn & garden Monitoring well								
Was a chemical/bacteriological sample submitted to Department? Yes No If yes, mo/day/yr sample was submitted								
1 mile Water well disinfected? 🔀 Yes 🗌 No								
5 TYPE OF CASING USED: Steel PVC Other								
CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to ft., Diameter in. to ft.								
Casing diameter								
TYPE OF SCREEN OR PERFORATION MATERIAL:								
☐ Steel ☐ Stainless Steel ☐ Other (Specify)								
Brass Galvanized Steel None used (open hole)								
SCREEN OR PERFORATION OPENINGS ARE:								
Continuous slot Mill slot Gauze wrapped Torch cut Drilled holes None (open hole) Louvered shutter Key punched Wire wrapped Saw cut Other (specify)								
SCREEN-PERFORATED INTERVALS: From								
From								
GRAVEL PACK INTERVALS: From								
Fromft. toft., Fromft. toft.								
6 GROUT MATERIAL: Neat cement Cement grout Bentonite Other								
Grout Intervals: From ft. to ft., From ft., From ft., From ft. to ft., From								
What is the nearest source of possible contamination: Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (specify below)								
Septic tank Lateral lines Pit privy Livestock pens Insecticide storage Other (s) Sewer lines Cesspool Sewage lagoon Fuel storage MAbandoned water well						er (specify below)		
Watertight sewer lines Seepage pit Feedyard Fertilizer storage Oil well/gas well								
Direction from well				from we				
FROM TO	LITHOLOG	IC LOG	FROM	ТО	LITHO. LO	OG (cont.) <u>or</u> PLU	GGING INTERVALS	
0 2 Tops			190	205	Tane	lay		
2 30 Tan c			205	<u> کا کات</u>	med-	Said		
30 40 fine	to med ::							
40 80 Tan	Sendy clay							
	country od	<u>ck</u>	-					
100 119 Med.	Sandy Clay							
	sana c rock + m.	- / Sin - /						
	c crumply						,	
7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was a constructed or a plugged								
under my jurisdiction and was completed on (mo/day/year)								
Kansas Water Well Contractor's License No								
under the business name of Sant ton Water William by (signature)								
INSTRUCTIONS: Use typewriter or ball point pen. PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks and check the correct inswers. Send three copies								
(white, blue, pink) to Kansas Department of Health and Environment, Bureau of Water, Geology Section, 1000 SW Jackson Sy., Suite 420, Topeka, Kansas 66612-1367. Telephone 785-296-5524. Send one copy to WATER WELL OWNER and retain one for your records. Include fee of \$5.00 for each constructed well. Visit us at								
http://www.kdheks.gov/waterwell/index.html. KSA 82a-1212								
KSA 82a-1212			Orig	gereat is	o avenuence, co	0 96156464		