USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

## WATER WELL RECORD KSA 82a-1201-1215

		ΙТ			
T	R	EW	sec 1/4	1/4	1/4 No.

Kansas State Dept. Of Health (Water Well Contractors) Forbes–Bldg. 740 Topeka, Kansas 66620

	County	Township name	Fraction	В	Section	on number		Town number	Range number	
1 Location of well:	Meade	Fowler	NÉ 40	SWX.		24		31	27	
Distance and direct	ion from nearest town or cit			3 Owner	r of well	: Leo	mard	Beckerman		
Street address of well location if in city:  Address					ess: Fowler, Kansas					
Locate with "X" in	section below:	Sketch map:							ate of completion 1-22-75	
	1 1 1							Il diameter <u>28</u> in.  Cable tool Rotary	Driven Dua	
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1						☐ Hollow rod ☐ Jetted ☐ Bored ☑ Reverse rotary			
w  !							6 Use: ☐ Domestic ☐ Public supply ☐ Industry  ☑ Irrigation ☐ Air conditioning ☐ Commercial			
,,							Test well			
							7 Casing: Material Height: above/below			
	1 <b>X</b> 1 1						Threaded Welded Surface 18 in. AB Diam. Weight lbs./ft			
	1 Mile			<del></del>		1	1	5 in. to 211 ft. depth Dr in. to ft. depth	rive shoe? Yes X No	
2	Тур	e and color of material			From	То	8 Scr	een;		
Bro	own and caled	he clay			0	24		nufacturer <b>Free-flo</b> be <b>10%</b> Di		
*	ne sand with		ed		24	37	Slo	be 10% Di t/gauze 1/8 Le	ngth Zn	
7.	llow and brow				37	81	Fitt	t/gauze 1/0 Le between 71 ft. and 2 tings: avel pack KYes No S	38% 券8	
God	od loose sand	and gravel			81	96	9 Stat	tic water level:  ft. below land surface		
	leche cla y a					112		nping level below land surface		
	lf medium san					115	20	00 ft. after <u>8</u> hrs. ft. after <u> </u>	pumping <b>275</b> g.p.m.	
							Esti	mated maximum yield 30	O g.p.m.	
Sar	ndy caleche c	lay			115	160		ter sample submitted: Yes  No Date		
Sar	ndrock and fi	ne sand with	30 to	40%				II head completion:		
	clay mixed				160	195			Inches above grade	
Sandy brown clay					195	100		Neat cement Bentonite		
bandy of own clay					- 7 )	- 22		arest source of possible con		
Fine brown sand & broken rock with							ft.	NA Direction	Type	
	10% clay mi	xed			199	208	15 Pur	Il disinfected upon complet	ion? Yes No Not installed	
Yel	low and tan	clay			208	211	Ma	nufacturer's nameHi		
Blu	e shale				211	220	1	gth of drop pipe ft		
	Rela	211 1	40				Тур		Turbine	
		a second sheet if needed)					_ =	Jet Certrifugal	Reciprocating Other	
16 Remarks: elevat								ter well contractor's certific		
							l .	s well was drilled under my ort is true to the best of my	'	
Topography:							Ac	e-Hi Drillin		
☐ Hill ☐ Slope	4.						Busi Ada	ness name dress Box 1442.	Dodge City. Ks.	
Upland							Į.	ned Gall G J #	Date 2-21-25	
☐ Valley							L			