

	R WELL		-	· · · · C-3	3860		ion of Wate			Wall ID	
Original Record Correction Change in 1 LOCATION OF WATER WELL: F			e in Well Use Resources App. No. Fraction Section Number				Township Numbe	Well ID	ge Number		
	County: $\frac{1}{4}$ $\frac{1}{4}$ $\frac{1}{4}$			/4 1/4	1 0			$\Box E \Box W$			
Business Address:	2 WELL OWNER: Last Name: First: Streed Business: Address: Address:					reet or Rural Address where well is located (if unknown, distance and ection from nearest town or intersection): If at owner's address, check here:					
,											
WITH	"X" IN		4 DEPTH OF COMPLETED WELL:								
NW -	ON BOX: N NE SE	Depth(s) Groundwater Encountered: 1) 2) 2) (a) (b) (c) (c) <td>Dry Wa ft. y-yr) ft. gpm ft.</td> <td colspan="3">y Well ft GPS (unit make/model: </td> <td>IAD 27) Io)</td>			Dry Wa ft. y-yr) ft. gpm ft.	y Well ft GPS (unit make/model: 			IAD 27) Io)		
	S			01	ft and		Source: Land Survey GPS Topographic M				
1	S Bore Hole Diameter: in. to in. to										
1. Domestic	e: ehold & Garden tock tion ot	BE USED AS: 5. Public Water Supply: well ID					 10. □ Oil Field Water Supply: lease 11. Test Hole: well ID □ Cased □ Uncased □ Geotechnical 12. Geothermal: how many bores? a) Closed Loop □ Horizontal □ Vertical b) Open Loop □ Surface Discharge □ Inj. of Water 13. □ Other (specify): 				
				itted to KDHE?	IYes □	No 1					
		? \Box Yes \Box				110 1	n yes, dao	c san	ipie was sublintee	4	
8 TYPE OF CASING USED: Steel PVC Other CASING JOINTS: Glued Clamped Welded Threaded Casing diameter in. to ft, Diameter in. to ft, Diameter in. to ft, Diameter Casing height above land surface in. Weight lbs./ft. Wall thickness or gauge No. ft. TYPE OF SCREEN OR PERFORATION MATERIAL: Steel Fiberglass PVC Other (Specify) Steel Brass Galvanized Steel Concrete tile None used (open hole) SCREEN OR PERFORATION OPENINGS ARE: Continuous Slot Mill Slot Gauze Wrapped Torch Cut Drilled Holes Other (Specify) Steel Louvered Shutter Key Punched Wire Wrapped Saw Cut None (Open Hole) SCREEN-PERFORATED INTERVALS: From ft. to ft. to ft. to ft. to ft. GRAVEL PACK INTERVALS: From ft. to ft. to ft. from ft. to ft. to ft.											
				Cement grout B							
Grout Intervals: From ft., From ft., From ft., From ft., From ft. to ft. Nearest source of possible contamination:											
10 FROM			ITHOLOG		FRO				HO. LOG (cont.) or	PLUGGIN	GINTERVALS
IU FROM		L					10				
	<u> </u>										
					NT - 4 -						
					Notes						
11 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was constructed, reconstructed, or plugged under my jurisdiction and was completed on (mo-day-year)											
-		eks.gov/waterwel		ater, Geology Section, I	1000 S W Jac		., June 420,	, rope	na, maiisas 00012-130/	-	A 82a-1212

Form	WWC5
Contractor	Hydro Resources Mid Continent, Inc.
Well Owner	
Doc ID	1333860

Litholgy

From	То	LithologicLog
0	2	top soil
2	9	brown sandy clay
9	20	light green clay
20	29	light green clay w/ some fine sand strips
29	83	blue clay
83	95	light blue clay w/ couple small sand beds
95	100	light blue & brown clay
100	126	blue clay w/ few small fine sand strips
126	140	blue clay
140	160	fine sand w/ many clay ledges
160	174	brown sandy clay w/ some sand strips
174	181	sand fine to med coarse
181	194	sand fine to med coarse w/ some clay stringers
194	202	sand fine to med coarse
202	210	fine sand w/ some clay stringers
210	226	brown rock & lime rock w/ few fine sand strips
226	235	brown sandy clay w/ few sand strips
235	260	fine sand w/ few brown rock & few small clay stringers

Form	WWC5
Contractor	Hydro Resources Mid Continent, Inc.
Well Owner	
Doc ID	1333860

Litholgy

From	То	LithologicLog
260	268	brown rock & fine sand
268	279	soapstone
279	300	shale