


1 LOCATION OF WATER WELL: Fraction NE 1/4 NE 1/4 SE 1/4 Section Number 26 Township Number T 31 S Range Number R 29 E/W
 County: MEADE Distance and direction from nearest town or city street address of well if located within city?
 1/4 Mile North of Missler, Kansas

2 WATER WELL OWNER: MERTILLA TOWNSHIP
 RR#, St. Address, Box #: c/o LARRY KANE, RFD #1 Board of Agriculture, Division of Water Resources
 City, State, ZIP Code: MEADE, KANSAS 67864 Application Number: ---

3 LOCATE WELL'S LOCATION WITH AN "X" IN SECTION BOX:  4 DEPTH OF COMPLETED WELL: 400 ft. ELEVATION: Slope
 Depth(s) Groundwater Encountered: 1 Not available ft. 2 ft. 3 ft.
 WELL'S STATIC WATER LEVEL: 210 ft. below land surface measured on mo/day/yr June 6, 1986
 Pump test data: Well water was ... ft. after ... hours pumping ... gpm
 Est. Yield: 20 gpm: Well water was ... ft. after ... hours pumping ... gpm
 Bore Hole Diameter: 9 7/8 in. to 400 ft., and ... in. to ... ft.
 WELL WATER TO BE USED AS: 5 Public water supply 8 Air conditioning 11 Injection well
 XX Domestic 3 Feedlot 6 Oil field water supply 9 Dewatering 12 Other (Specify below)
 2 Irrigation 4 Industrial 7 Lawn and garden only 10 Observation well
 Was a chemical/bacteriological sample submitted to Department? Yes.....No XX.....; If yes, mo/day/yr sample was submitted Water Well Disinfected? Yes XX No

5 TYPE OF CASING USED: 5 Wrought iron 8 Concrete tile CASING JOINTS: Glued XX Clamped
 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Welded
 XXX PVC 4 ABS 7 Fiberglass Threaded
 Blank casing diameter: 5 in. to 360 ft., Dia. ... in. to ... ft., Dia. ... in. to ... ft.
 Casing height above land surface: 15 in., weight 2.8 lbs./ft. Wall thickness or gauge No. 265
 TYPE OF SCREEN OR PERFORATION MATERIAL: XXX PVC 10 Asbestos-cement
 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 11 Other (specify)
 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 12 None used (open hole)
 SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped XXX Saw cut 11 None (open hole)
 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes
 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)
 SCREEN-PERFORATED INTERVALS: From 360 ft. to 400 ft., From ... ft. to ... ft.
 GRAVEL PACK INTERVALS: From 14 ft. to 400 ft., From ... ft. to ... ft.

6 GROUT MATERIAL: XX Neat cement 2 Cement grout 3 Bentonite 4 Other
 Grout Intervals: From 4 ft. to 14 ft., From ... ft. to ... ft., From ... ft. to ... ft.
 What is the nearest source of possible contamination: 10 Livestock pens 14 Abandoned water well
 XXX Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage 15 Oil well/Gas well
 2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage 16 Other (specify below)
 3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide storage
 Direction from well? South How many feet? 100

FROM	TO	LITHOLOGIC LOG	FROM	TO	LITHOLOGIC LOG
0	3	Topsoil			
3	27	Clay			
27	51	Caliche			
51	67	Fine Sand			
67	96	Caliche			
96	161	Med. to Lar. Sand			
161	172	Clay			
172	400	Med. to Lar. Sand & Gravel			

7 CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was completed on (mo/day/year) June 11, 1986 and this record is true to the best of my knowledge and belief. Kansas Water Well Contractor's License No. 252 This Water Well Record was completed on (mo/day/year) June 26, 1986 under the business name of FRIESEN WINDMILL & SUPPLY INC. by signature

INSTRUCTIONS: Use typewriter or ball point pen, PLEASE PRESS FIRMLY and PRINT clearly. Please fill in blanks, underline or circle the correct answers. Send top three copies to Kansas Department of Health and Environment, Division of Environment, Environmental Geology Section, Topeka, KS 66620. Send one to WATER WELL OWNER and retain one for your records.

1986000000-50

OFFICE USE ONLY
T
R
EW
SEC.