


USE TYPEWRITER OR BALL POINT PEN—PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and Environment—Division of Environment (Water well Contractors) Topeka, Kansas 66620

1. Location of well:	County Meade County	Section NW 1/4 NW 1/4 NW 1/4	Section number 27	Township number T 31 S R 29	Range number 29
2. Distance and direction from nearest town or city: From Meade 5 West to the Missler Rd. go 4 North, 2 West, 1 South in the Northwest corner		3. Owner of well: Jack Berghaus 415 N. Webb City, state, zip code: Meade, KS 67864			
4. Locate with "X" in section below: 		Sketch map:		6. Bore hole dia. 26 in. Completion date 12-29-78 Well depth 385 ft.	
5. Type and color of material		From		To	
		7. <input type="checkbox"/> Cable tool <input type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input checked="" type="checkbox"/> Reverse rotary			
		8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input type="checkbox"/> Industry <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input type="checkbox"/> Oil field water <input type="checkbox"/> Other			
		9. Casing: Material Steel Height: Above or below Threaded <input type="checkbox"/> Welded <input checked="" type="checkbox"/> Surface 1 ft. in. RMP <input type="checkbox"/> PVC <input type="checkbox"/> Weight 36.87 lbs./ft. Dia. 16 in. to 385 ft. depth Wall Thickness: inches or Dia. <input type="checkbox"/> in. to <input type="checkbox"/> ft. depth gage No. .219			
		10. Screen: Manufacturer's name Johnson Type Johnson Galy. 100-16" Slot/gauze 0-200 Plain, 200-240 Perf. Set between 240-250 Screen and 250-300 Perf. 300-330 Screen and 330-385 Perf. ft. Gravel pack? yes Size range of material 1/2 to 5/8			
		11. Static water level: <input type="checkbox"/> mo./day/yr. 140 ft. below land surface Date 1-11-79			
		12. Pumping level below land surfaces: 147 ft. after 2 hrs. pumping 750 g.p.m. 153 ft. after 4 hrs. pumping 1850 g.p.m. Estimated maximum yield 1850 g.p.m.			
		13. Water sample submitted: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No Date			
		14. Well head completion: <input type="checkbox"/> Pitless adapter 1 ft. inches above grade			
		15. Well grouted? Yes With: <input type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input checked="" type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.			
16. Nearest source of possible contamination: ft. <input type="checkbox"/> Direction N/A Type <input type="checkbox"/> Well disinfected upon completion? <input type="checkbox"/> Yes <input type="checkbox"/> No					
17. Pump: <input type="checkbox"/> Not installed Manufacturer's name Gould 3 stg. 14" JHC Model number <input type="checkbox"/> HP <input type="checkbox"/> Volts <input type="checkbox"/> Length of drop pipe 200 ft. capacity 1200 g.p.m. Type: <input type="checkbox"/> Submersible <input checked="" type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other					
18. Elevation:	19. Remarks:		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Minter Wilson Drilling Co. 208 Business name License No. 1/4 NW 1/4 NW Address Box A, Garden City, KS 67846 Signed [Signature] Date 6/27/79 Authorized representative		

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5

Phone 276-8269 • P.O. Box A • GARDEN CITY, KANSAS 67846

December 8, 1978

Jack Berghaus
Meade County

Location: N. W. $\frac{1}{4}$ 27-31-29 From Meade 5 West to the Missle:
Road go 4 mile North, 2 mile West 1 mile South in
Northwest corner

Static Water Level - 140

Test #

0	8	Top Soil
8	72	Brown Sandy Clay mixed with Rock Hard
72	84	Fine to med. sand and gravel (loose)
84	91	Fine to med. sand and gravel streak of coarse gravel (loose)
91	103	Brown Sandy Clay
103	132	Fine to med. sand and gravel (loose)
132	136	Fine to med. sand and gravel (hard)
136	149	Fine to med. sand and gravel (loose)
149	166	Brown Clay
166	258	Fine to med. sand and gravel
258	267	Fine to med. sand and gravel 15% Clay streak
267	275	Fine to med. sand (loose)
275	334	Fine to med. sand and gravel (loose)
334	348	Blue Clay
348	355	Fine to med. sand and gravel (loose)
355	361	Brown Clay Rock Hard Pull Down
361	366	Med. Sand and Gravel (loose)
366	377	Brown Sandy Clay (hard)
377	382	Fine to med. sand and gravel
382	417	Brown Sandy Clay Brown Rock mixed
417	427	Fine Sand Tight
427	434	Brown Sandy Clay
434	471	Brown Sandy Clay 20% Sand no good
471	500	Red Clay Hard Pull Down

T. D. 385'