WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	Country	Fraction			Santian		Township number Range number			
1. Location of well:	County				Section number		· ·	Range number		
	MEADE	SE 1/4 NW		3/4	28	22	T 31 s	R 29	/ /W	
2. Distance and direc	ction from nearest town or city: 🍕	south 🧺 wes	t .	3. Own	er of well:		oy Mhitehead			
Street address of well location if in city: R.R. or street City, state,						Meade, Ks. 67864				
		76								
4. Locate with "X" in		6. Bore hole dia, 26 in. Well depth 110 ft.	Completion date	0-25-10						
T T	. 7									
NW NE							7Cable toolRotaryDrivenDugHollow rodJettedBoredX Reverse rotary			
							8. Use: Domestic Public supply Industry			
W							Irrigation Air			
							Lawn Oi	l field water C	Other	
							9. Casing: Material <u>stee</u>			
	1						Threaded Welded _ RMP PVC	Surface 12	in.	
1 Mi							Dia.a in. to 1.a.a ft. dept	h!Wall Thickness: ir	iches or	
5. Type and color of material				From	Dia. 16 in. to 177 ft. depth Wall Thickness: in Dia. in. to ft. depth gage No.					
							10. Screen: Manufacturer's no Johnson Divi	ome. Sion		
							Type Galv.			
							Slot/gauze 100	_ Length20) 1	
						Per	Set between <u>380</u> F <u>180-320</u> ft. a	ft. and 100 nd 350-380,	1,00 ft.	
						ندن ش	Gravel pack?VOS Size ran			
							11. Static water level:		./day/yr.	
								ace Date <u>5-1</u>	9-76	
							12. Pumping level below land		,	
							150 ft. after 3 h	rs. pumping 1475	_ g.p.m.	
							Estimated maximum yield	475	_ g.p.m.	
							13. Water sample submitted:		./day/yr.	
							Yes 🔀 No 🛭	Date		
							14. Well head completion:	70 11 1	.	
								12 Inches above		
		· · · · · · · · · · · · · · · · · · ·					15. Well grouted? <u>VAS</u> With: Neat cement	Bentonite	Concrete	Ų
					 		Depth: From ft. t	ft.		-
							16. Nearest source of possible	contamination 1/		
							ft Direction Well disinfected upon comple		X No	
					\vdash		17. Pump:			10
							Manufacturer's name Goul			5
							Model number 121B	_ HP200 Vo	1 (_ _
							Length of drop pipe 200 Type:	_ ft. capacity 100	₩.p.m.	"(
							Submersible	Turbin	e L	
							Jet		ocating S	7
10 51 11	(Use a second s	neer if needed)			Ц Ц		Centrifugal	Other		Ĉ
18. Elevation:	19. Remarks:						20. Water well contractor's c This well was drilled under my		s report	
							is true to the best of my know	ledge and belief.		^
Topography:							Minter Wilson			η
Hill							Business nomP.O. Box	Garden G	Series 1 5	9
Upland						٩	Attened	De Del	9-16	200
Valley						1	Authorized repr	esentative	121	7

Phone 276-8269 • P.O. Box 493 • GARDEN CITY, KANSAS 67846

ROY WHITEHEAD
MEADE COUNTY
4-26-76

Location: SE 28-31-29

From Missler Elevator first road south, 2 miles west, & mile north, & mile east, 30 ft. west of

Pivot.

Static Water Level: 140'

Test # 1

0 3 5 20 124	3 5 20 124 140	Top Soil Brown Clay Brown Sandy Clay Brown & White Sandy Clay Brown & White Clay, Streaks of Fine to Med. Sand & Gravel (30%)
140	190	Fine to Med. Sand & Gravel (Loose)
190	198	Fine to Med. Sand & Gravel, Streaks of white Rock
190	170	(10%)
198	308	Fine to Med. Sand & Gravel (Loose)
308	316	Fine to Med. Sand, Streaks of Clay (Blue & Brown
500	<i>J</i>	20%)
316	350	Blue & Brown Clay
350	1,00	Fine to Med. Sand & Gravel (Loose)
	410	Fine to Med. Sand & Gravel, Streaks of Clay (10%)
400	4. •	(Loose)
410	1427	Brown, White & Gray Clay
427	430	Yellow & Gray Clay (Tight)
44	450	TOTTON OF OTAL OTAL
		T.D 410'