1 LOCATION OF WATER WELL:			FRACTION	water Well Rec	cord Form WWC-	Section Number	Township Number	Range Number	
∸ Sumner			SE 1/4	NW 1/4	NW 1/4	4	2.1	214	
Sumner SE 1/4 NW 1/4 NW 1/4 Q T 31 s R 3W E/W  Distance and direction frem nearest town or city street address of well if located within city?									
•									
1 m. West, 1280' S., 900' East of Conway Springs, Kansas  2 WATER WELL OWNER: GERBER, Leo									
	T. ADRESS,	011/201		0 1			Board of Agriculture, D	ivivsion of Water Resource	
,	,	1111 112 /			_				
CITY, STATE, ZIP CODE: Conway Springs, Kansas  Application Number:  3 LOCATE WELL'S LOCATION WITH 4 DEPTH OF COMPLETED WELL 52 & FLEVATION.									
COLORATE WELL'S LOCATION WITH   OPENTH OF COMPLETED WELL   S2 ft.   ELEVATION:   Depth(s) groundwater Encountered   1 ft.   2 ft.   3 ft.   3 ft.   1 ft.   2 ft.   3 ft.									
t			, .				FACE MEASURED ON mo/day/yr	12/27/1994	
			LL'S STATIC \ Pump te	WATER LEVEL			_		
•	Xw	NE.	-		ll water was		nfter hours pum	·	
ile	i		Yield	Br	ell water was		after hours pum		
M Mile	<del></del>		Hole Diameter		to 52	ft.	and in.	to ft.	
		1 ! 1 1		BE USED AS:	5 Public wat			njection well Other (Specify below)	
1	sw	SE	1 Domestic	3 Feedlot 4 Industrial	6 Oil field w		-	other (specify below)	
		1 ! ! ! !	2 Irrigation		7 Lawn and	-	0 Monitoring well		
<b>↓</b>	Was a chemical/bacteriological sample submitted to Department? Yes No X ; If yes, mo/day/yr sample was								
S submitted Water Well Disinfected? Yes X No									
		SING USED:		5 Wrought iro	on	8 Concrete tile	CASING JOINTS: G	Hued X Clamped	
1 Stee		3 RMP (SR)		6 Asbestos-Cei	ment	9 Other (Specify be	,	Velded	
2 PVC	!	4 ABS		7 Fiberglass	5	SDR-26	Т	Threaded	
Blank ca	sing Diam	eter 5 in.	to 37	ft., Dia	ir	ı. to	ft., Dia in.	to ft.	
Casing height above land surface 12 in., weight 2.35 lbs./ft. Wall thickness or gauge No214									
TYPE C	F SCREE	N OR PERFORATION	N MATERIAL:			7 PVC	10 Asbestos-ceme	ent	
1 Stee	1	3 Stainless Steel		5 Fiberglass		8 RMP (SR)	11 other (specify	7)	
2 Bras	S	4 Galvanized steel		6 Concrete tile		9 ABS	12 None used (o)	pen hole)	
SCREE	N OR PER	REFORATION OPENIN	G ARE:	5 G	auzed wrapped		8 Saw cut	11 None (open hole)	
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drilled holes									
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify)									
A Total Carlo									
						ft., From ft., From			
from  GRAVEL PACK INTERVALS: from 24					ft. to			ft.	
	GRAVI	EL PACK INTERVAL	_	4	ft. to 52		ft. to	ft.	
from ft. to ft., From ft. to ft.  6 GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other									
Count Internal of Paris A									
Grout Intervals: From 4 ft. to 24 ft. From ft. to ft. From ft. to  What is the nearest source of possible contamination: 10 Livestock pens 14 Abandon water well									
1 Septic tank 4 Lateral lines				7 Pit priv	7 Pit privy				
			_	- '	8 Sewage lagoon		13.	Oil well/Gas well Other (specify below)	
C CESS POOI							cide storage	16 Other (specify below)	
5 waterught sewer lines 6 Seepage pit 9 reedyard									
Direction from well? West How many feet? 100  FROM TO LITHOLOGIC LOG FROM TO PLUGGING INTERVALS									
	TO		HOLOGIC LO	J	FROM	TO TO	PLUGGING INTE	KVALS	
0	2	topsoil							
2	35	fine sand	•						
35	52	medium san	<u>a</u>				- manner		
ļ									
	<u>.</u> .								
7 CON	TRACTO	R'S OR LANDOWNER'S C	ERTIFICATION: T	his water well wa	s (1) construc	cted. (2) reconstru	ucted, or (3) plugged under r	ny jurisdiction and	
was completed on (mo/day/year)									
Well Contractor's License No236									
Under the business name of Harp Well & Pump Service, Inc by (signature)									

Jane Frederick