USE TYPEWRITER OR BALL POINT PEN-PRESS FIRMLY, PRINT CLEARLY.

WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County	Fraction		Section number		Township number	Range number	
1. Location of well:	Meade	SE 1/4 NE 1/4 NE 1/4		17		т 31 s	r 30 4 /	w.l
1 27 5 11 2 11 2 11 2 11 2 11 2 11 2 11				er of well:		E. G. (Butch) Amerin		:
Street address of well location if in city: R.R. or City, str				tate, zip code:		Plains, Kansas		
4. Locate with "X" in section below: Sketch map:						6. Bore hole dia 9 7/8in	. Completion date	_
N						Well depth 300 ft.		
X-3NWN							Driven Dug Bored Reverse rot	ary
i'						8. Use: X Domestic _ P		Í
W						Irrigation Air conditioning Stock Lawn Oil field water Other		
sw se						9. Casing: Material RMD Height: Above or below		
 						Threaded Welded X Surface 24 in.		
S						RMPPVCWeight220_lbs./ft_00 Diain. toft. depth!Wall Thickness: inches or		
5. Type and color of material				From	То	Diain. toft. depth gage No320		
				-		10. Screen: Manufacturer'sJess & Lo	owell	_
Top soil				0	3	Type RMP	Dia5t1	_
Green clay				3	21	Slot/gauze 1/8!! Set between 120	700	- fr.
Tan & white clay with streaks of fine sand				21	85	Gravel pack? Yes Size ro		ft.
•						11. Static water level:	mo./day/	-
Med. to lar. sand, gravel, & tan clay streaks				s 85	112	ft. below land su		
Med. to lar. sand				112	160	12. Pumping level below lan	d surfaces: hrs.pumpingg.p.i	.
Yellow clay and gravel				160	181	ft. after	hrs. pumping g.p.:	1
				127	192	Estimated maximum yield		
Med. to lar. sand				101	192	Yes <u>X</u> No	Date	
Tan clay and med. to lar. sand & gravel				192	217	14. Well head completion: X Pitless adapter	Inches above grade	
Sandy tan & white clay with gravel streaks				217	261	15. Well grouted? yes		T 166
Blue clay with gravel				261	272	With: Neat cement Depth: From ft. to	BentoniteX_ Concre	• - [~
								$\dashv \vdash$
Blue clay & sandy clay				-	280	16. Nearest source of possible contamination: ft Direction Type		
Tan clay & med. to lar. sand				280	305	Well disinfected upon compl	Not installed	$\mathbb{P}^{\mathbb{P}}$
				ļ <u>.</u>		Manufacturer's nameA	rmotor	- "10
						Model number <u>SD12=150</u> HP <u>1½</u> Volte20 Length of drop pipe <u>231</u> ft. capacity <u>10</u> g.p.m.		
						Туре:		
						Submersible Jet	Turbine Reciprocating	
(Use a second sheet if needed)					L	Centrifugal	Other	- * ' '
18. Elevation: 19. Remarks:						20. Water well contractor's certification: This well was drilled under my jurisdiction and this report		
Tonography						is true to the best of my knowledge and belief.		
Topography:						Friesen Windmi Business name	252 License N	—ı · ·
Slope						Address Meade	Kansas 6786	- 3/2
Valley						Signed Authorized re	presentative Date 2-1	ZZ
Forward the white, blu	e and pink copies to the Department		Form WWC-5	II.				