County: Seward S 1/2 S 1/2 NW 1/4 11 T Distance and direction from nearest town or city street address of well if located within city? 2 WATER WELL OWNER: Phyllis Krause RR#, St. Address, Box # : 105 W Greensboro St. City, State, ZIP Code Plains, Ks 67869 3 LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered 1 ft. 2 WELL'S STATIC WATER LEVEL Na ft. below land surface me Pump test data: Well water was ft. after Pump test data: Well water was ft. after Set. Yield gpm: Well water was ft. after In Domestic 3 Feed lot 6 (a) Oil field water supply 9 De 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted 5 TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Blank casing diameter 4.5 in. to 255 ft. Dia in. to ft. Dia Casing height above land surface 18 in., weight 2.38 tilbs./ft. Wall thick TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille	of Agriculture, Division of Water Resources ation Number: 20050113 ft. 3 ft. assured on mo/day/yr hours pumping gpm hours pumping gpm in. to conditioning 11 Injection well watering 12 Other (Specify below) ionitoring well No X If yes, mo/day/yr sample was isinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. consist or gauge No
WATER WELL OWNER: Phyllis Krause R#, St. Address, Box # : 105 W Greensboro St. Board Applic LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: N Depth (S) Groundwater Encountered 1 ft. 2 WELL'S STATIC WATER LEVEL Na ft. after Est. Yield gpm: Well water was ft. after Est. Yield gpm: Well water was ft. after Est. Yield gpm: Well water supply 9 De 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted Water Static Water Static Water Well Depth (S) Groundwater Static Water Supply 9 De 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted Water Well Depth (S) Groundwater Static Well water supply 9 De 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted Water Well Depth (S) Groundwater Static Water Well Depth (S) Groundwater Static Well water supply 9 De 3 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Slank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia lasing height above land surface 18 in., weight 2.38 Depth (SR) 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS 3 CREEN OR PERFORATION OPENINGS ARE: 6 Gonzele tile 9 ABS 4 CREEN OR PERFORATION OPENINGS ARE: 6 Gonzele tile 9 ABS 5 CREEN OR PERFORATION OPENINGS ARE: 7 Torch cut 10 Othe 6 CREEN-PERFORATED INTERVALS: From 2 5 ft. to 3 3 5 ft. From 6 GRAVEL PACK INTERVALS: From 2 6 ft. to 3 3 5 ft. From 7 From ft. to 3 6 Public water 4 Others CRECIT MATERIAL 1 Next correct CRECIT MATERIAL 1 N	of Agriculture, Division of Water Resources ation Number: 20050113 ft. 3 ft. assured on mo/day/yr hours pumping gpm hours pumping gpm in. to conditioning 11 Injection well watering 12 Other (Specify below) ionitoring well No X If yes, mo/day/yr sample was isinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. consist or gauge No
WATER WELL OWNER: Phyllis Krause R#, St. Address, Box #: 105 W Greensboro St. I State, ZIP Code Plains, Ks 67869 Depth (S) Groundwater Encountered 1 ft. 2 WELL'S STATIC WATER LEVEL Na ft. below land surface me Pump test data: Well water was ft. after Pump test data: Well water was ft. after Pump test data: Well water was ft. after Pump test data: Well water supply 8 A Air NOWLL WATER TO BE USED AS: 5 Public water supply 8 Depth (S) Trype OF BLANK CASING USED: 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes Submitted Water was ft. after Pump test data: Well water was ft. after Bore Hole Diameter 8 in. to 340 ft. and WELL WATER TO BE USED AS: 5 Public water supply 9 De 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes Submitted Water was ft. after WELL WATER TO BE USED AS: 5 Public water supply 9 De 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes Submitted Water was ft. after WELL WATER TO BE USED AS: 5 Public water supply 9 De 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes Water Well D 2 PVC 4 ABS 7 Fiberglass In. to ft. Dia in. to ft. Dia Sing height above land surface 18 in., weight 2.38 ibs./ft. Wall thick YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drill CREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to 3.4.0 Checkenstee	ft. 3 ft. assured on mo/day/yr hours pumping gpm hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) ionitoring well No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. coness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
R#, St. Address, Box #: 105 W Greensboro St. ty, State, ZIP Code Plains, Ks 67869 Applic LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: Depth (s) Groundwater Encountered 1 ft. 2 WELL'S STATIC WATER LEVEL	ft. 3 ft. assured on mo/day/yr hours pumping gpm hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) ionitoring well No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. coness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
Ref., St. Address, Box # 105 W Greensboro St. Ity, State, ZIP Code Plains, Ks 67869 Applic LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: N Depth(s) Groundwater Encountered 1 ft. 2 WELL'S STATIC WATER LEVEL 11 ft. after Pump test data: Well water was ft. after Pump test data: Well water was ft. after Est. Yield gpm: Well water was ft. after Pump test data: Well water was ft. after Est. Yield gpm: Well water was ft. after Est. Yield g	ft. 3 ft. assured on mo/day/yr hours pumping gpm hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) ionitoring well No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. coness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
Application of the property of	ft. 3 ft. assured on mo/day/yr hours pumping gpm hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) ionitoring well No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. coness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
LOCATE WELL'S LOCATON WITH AN "X" IN SECTION BOX: Depth(s) Groundwater Encountered	ft. 3 ft. pasured on mo/day/yr hours pumping gpm hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) lonitoring well No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. kness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
Depth(s) Groundwater Encountered 1 Depth(s) Groundwater Encountered 1 Depth(s) Groundwater Encountered 1 Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 1 Pump test data: Well water was 1 Est. Yield 1 Bore Hole Diameter 1 Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 1 Pump test data: Well water was 1 Est. Yield 1 Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 1 Pump test data: Well water was 1 Est. Yield 1 Depth(s) Groundwater Encountered 1 WELL'S STATIC WATER LEVEL 1 Bore Hole Diameter 8 In. to 340 ft. after 1 WELL WATER TO BE USED AS: 5 Public water supply 9 Der 1 1 Domestic 3 Feed lot 6 Oli field water supply 9 Der 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted Water Well Derection 10 Mater Well Derection 10 Other (specify below) Type OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI 1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) Type OF SCREEN OR PERFORATION MATERIAL: 7 PVC 1 Steel 3 Stainless steel 1 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other (specify below) 10 Other (sp	ft. 3 ft. pasured on mo/day/yr hours pumping gpm hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) contoring well No X If yes, mo/day/yr sample was disinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. consess or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 14 Cut 11 None (open hole) 15 cut 11 None (open hole) 16 cut 55 conservations 17 conservations 18 ft. to ft.
Depth(s) Groundwater Encountered 1 ft. 2 WELL'S STATIC WATER LEVEL na ft. below land surface me Pump test data: Well water was ft. after Bore Hole Diameter 8 in. to 340 ft. and WELL WATER TO BE USED AS: 5 Public water supply 8 Air 1 Domestic 3 Feed lot 6 Oil field water supply 9 De 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted Water Well D TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI OF TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI Delank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Bank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Casing height above land surface 18 in., weight 2.38 ibs./ft. Wall thick TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drills 2 Louvered shutter 4 Key punched 7 Torch cut 10 Othe GCREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3.5 ft. From From ft. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 6. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 6. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 6. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 6. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 6. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 6. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 6. to 7 Torch cut 10 Othe From ft. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 6. to 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 7 Torch cut 10 Othe From 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 6. to 7 Torch cut 10 Othe From 7 Torch cut 10 Othe GRAVEL PACK INTERVALS: From 7 Torch cut 10 Othe From 7 Torch cut 10 O	ft. 3 ft. pasured on mo/day/yr hours pumping gpm hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) contoring well No X If yes, mo/day/yr sample was disinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. consess or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 14 Cut 11 None (open hole) 15 cut 11 None (open hole) 16 cut 55 conservations 17 conservations 18 ft. to ft.
WELL'S STATIC WATER LEVEL 13 ft. below land surface me Pump test data: Well water was ft. after Bore Hole Diameter 8 in. to 340 ft. and WELL WATER TO BE USED AS: 5 Public water supply 9 Der 1 Domestic 3 Feed lot 6 Oil field water supply 9 Der 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted was a chemical/bacteriological sample submitted to Department? Yes submitted 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Blank casing diameter 4.5 in. to 255 ft. Dia in. to ft. Dia Casing height above land surface 18 in., weight 2.38 lbs./ft. Wall thick YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drill 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other GRAVEL PACK INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From ft. From ft. To contribute ft. Paces ft. From ft. From ft. From ft. From ft. From ft. To contribute ft. Paces ft. From ft. F	hours pumping gpm hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) lonitoring well No X If yes, mo/day/yr sample was lisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. cness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
Pump test data: Well water was ft. after gpm: Well water was ft. after st. Yield gpm: Well water was ft. after well water was ft. after set. Yield gpm: Well water was ft. after set. Yield gpm: Well water was ft. after set. Yield gpm: Well water supply ft. and water supply gpm: Well water supply gpm: Vell water supply gp	hours pumping gpm hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) lonitoring well No X If yes, mo/day/yr sample was lisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. cness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
Est. Yield gpm: Well water was ft. after Bore Hole Diameter 8 in. to 340 ft. and WELL WATER TO BE USED AS: 5 Public water supply 9 Der 1 Domestic 3 Feed lot 6 Oil field water supply 9 Der 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted Water Well D TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Blank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia lasing height above land surface 18 in., weight 2.38 lbs./ft. Wall thick TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS GCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drill 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other GCREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From ft. From From ft. to ft. From ft. From ft. From ft. The property of ft. From ft. From ft. The property of ft. The pro	hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) lonitoring well No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. cness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
Est. Yield gpm: Well water was ft. after Bore Hole Diameter 8 in. to 340 ft. and WELL WATER TO BE USED AS: 5 Public water supply 9 Der 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted Water Well D TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) PVC 4 ABS 7 Fiberglass Slank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Casing height above land surface 18 in., weight 2.38 ibs./ft. Wall thick TYPE OF SCREEN OR PERFORATION MATERIAL: 7/PVC 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other SCREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From	hours pumping gpm in. to ft. conditioning 11 Injection well watering 12 Other (Specify below) lonitoring well No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. cness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
Bore Hole Diameter 8 in. to 340 ft. and WELL WATER TO BE USED AS: 5 Public water supply 8 Air 1 Domestic 3 Feed lot 6 Oil field water supply 9 Der 2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted 10 Part Water Well D S TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI	in. to ft. conditioning 11 Injection well 12 Other (Specify below) ionitoring well No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. cness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) or cut 11 None (open hole) and holes er (specify) ft. to ft.
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Blank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Casing height above land surface 18 in., weight 2.38 lbs./ft. Wall thick TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other SCREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From	No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. Kness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 10 cut 11 None (open hole) 11 ed holes 12 er (specify) 13 ft. to ft.
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Blank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Casing height above land surface 18 in., weight 2.38 lbs./ft. Wall thick TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other SCREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From	No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. Kness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 10 cut 11 None (open hole) 11 ed holes 12 er (specify) 13 ft. to ft.
2 Irrigation 4 Industrial 7 Lawn and garden (domestic) 10 M Was a chemical/bacteriological sample submitted to Department? Yes submitted TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 7 Fiberglass Blank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Casing height above land surface 18 in., weight 2.38 lbs./ft. Wall thick TYPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS SCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other SCREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From	No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. Kness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 10 cut 11 None (open hole) 11 ed holes 12 er (specify) 13 ft. to ft.
Was a chemical/bacteriological sample submitted to Department? Yes submitted S	No X If yes, mo/day/yr sample was bisinfected? Yes X No NG JOINTS: Glued X Clamped Welded Threaded in. to ft. cness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) out 11 None (open hole) and holes er (specify) ft. to ft.
S submitted Water Well D TYPE OF BLANK CASING USED: 5 Wrought Iron 8 Concrete tile CASI Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) PVC 4 ABS 7 Fiberglass Blank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Casing height above land surface 18 in., weight 2.38 Ibs./ft. Wall thick PVC SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other CREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3.5 ft. From From ft. to ft. From From ft. From From ft. to ft. From From ft. From	NG JOINTS: Glued X Clamped Welded Threaded in. to ft. Kness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 10 cut 11 None (open hole) 11 ed holes 12 er (specify) 13 ft. to ft.
TYPE OF BLANK CASING USED: Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) PVC 4 ABS 7 Fiberglass Blank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Basing height above land surface 18 in., weight 2.38 lbs./ft. Wall thick PVE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS BCREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drille CREEN OR PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3.5 ft. From From ft. to ft. From	Welded Threaded in. to the second of the
1 Steel 3 RMP (SR) 6 Asbestos-Cement 9 Other (specify below) 2 PVC 4 ABS 7 Fiberglass Ilank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia asing height above land surface 18 in., weight 2.38 lbs./ft. Wall thick YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other CREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3.5 ft. From From ft. to ft. From	Welded Threaded in. to ft. tness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 10 cut 11 None (open hole) 11 ed holes 12 er (specify) 13 ft. to ft.
2 PVC 4 ABS 7 Fiberglass Flank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Rasing height above land surface 18 in., weight 2.38 ibs./ft. Wall thick YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 9 Drille 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other From ft. to ft. From GRAVEL PACK INTERVALS: From 2.5 ft. to 3.3.5 ft. From From ft. to ft. From	Threaded in. to ft. to sness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 11 None (open hole) 12 ded holes 13 respecify) 14 ft. to ft.
Blank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia Casing height above land surface 18 in., weight 2.38 in., weigh	Threaded in. to ft. to sness or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) 11 None (open hole) 12 ded holes 13 respecify) 14 ft. to ft.
Stank casing diameter 4.5 in. to 255 ft., Dia in. to ft., Dia casing height above land surface 18 in., weight 2.38 ibs./ft. Wall thick the casing height above land surface 18 in., weight 2.38 ibs./ft. Wall thick the casing height above land surface 18 in., weight 2.38 ibs./ft. Wall thick the casing height above land surface 19 in. to ft. From 19 in. to ft., Dia in	in. to ft. tress or gauge No248 10 Asbestos-cement 11 Other (specify) 12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
Ibs./ft. Wall thick YPE OF SCREEN OR PERFORATION MATERIAL: 1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other CREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3 ft. From From ft. to ft. From From ft. From From ft. to ft. From From ft. to ft. From From ft. From From ft. From From ft. to ft. From	kness or gauge No
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other CREEN-PERFORATED INTERVALS: From 2.5.5 ft. to 3.3.5 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3.5 ft. From From ft. to ft. From	11 Other (specify) 12 None used (open hole) 12 tut 11 None (open hole) 13 ed holes 14 er (specify) 15 ft. to ft.
1 Steel 3 Stainless steel 5 Fiberglass 8 RMP (SR) 2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other CREEN-PERFORATED INTERVALS: From 2.5.5 ft. to 3.3.5 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3.5 ft. From From ft. to ft. From	11 Other (specify) 12 None used (open hole) 12 tut 11 None (open hole) 13 ed holes 14 er (specify) 15 ft. to ft.
2 Brass 4 Galvanized steel 6 Concrete tile 9 ABS CREEN OR PERFORATION OPENINGS ARE: 5 Gauzed wrapped 1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Other CREEN-PERFORATED INTERVALS: From 2.5 ft. to 3.3 5 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3.5 ft. From From ft. to ft. From	12 None used (open hole) cut 11 None (open hole) ed holes er (specify) ft. to ft.
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Othe CREEN-PERFORATED INTERVALS: From 255 ft. to 335 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 20 ft. to 335 ft. From From ft. to ft. From From ft. to ft. From GROUT MATERIAL: 1 Next correct 2 Correct grout 3 Postsorite A Other	cut 11 None (open hole) ed holes er (specify) ft. to ft.
1 Continuous slot 3 Mill slot 6 Wire wrapped 9 Drille 2 Louvered shutter 4 Key punched 7 Torch cut 10 Othe CREEN-PERFORATED INTERVALS: From 255 ft. to 335 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 20 ft. to 335 ft. From From ft. to ft. From From ft. to ft. From GROUT MATERIAL: 1 Next correct 2 Correct grout 3 Postsorite A Other	ed holes er (specify)ft. toft.
2 Louvered shutter 4 Key punched 7 Torch cut 10 Other CREEN-PERFORATED INTERVALS: From 2.5.5 ft. to 3.3.5 ft. From From ft. to ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3.5 ft. From From ft. to ft. From From ft. to ft. From St. Corport grout 3 Co	er (specify) ft. to ft.
GRAVEL PACK INTERVALS: From 2.55 ft. to 3.35 ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.35 ft. From From ft. to 3.35 ft. From From ft. to 6.5 GROUT MATERIAL: 1 Next cement 2.5 Cement grout 2.5 Cement grout 3.5 GROUT MATERIAL: 1 Next cement 2.5 Cement grout 3.5 GROUT MATERIAL: 1 Next cement 3.5 Cement grout 3.5 GROUT MATERIAL: 1 Next cement 3.5 Cement grout 3.5 GROUT MATERIAL: 1 Next cement 3.5 Cement grout 3.5 GROUT MATERIAL: 1 Next cement 3.5 GROUT MATERIAL: 1 Next c	ft. to ft.
From ft. to ft. From GRAVEL PACK INTERVALS: From 2.0 ft. to 3.3.5 ft. From From ft. to ft. From GROUT MATERIAL: 1 Next cement 2 Corport grout 2 Represent 4 Other	ft. toft.
From ft. to ft. From GROUT MATERIAL: 1 Next cement 2 Company grout 2 Postsoits 4 Other	
From ft. to ft. From 6 GROUT MATERIAL: 1 Next cement 2 Coment grout 2 Pontonito 4 Other	ft. to ft.
From ft. to ft. From GROUT MATERIAL: 1 Next cement 2 Corport grout 2 Postcoite 4 Other	ft to ft
GROUT MATERIAL: 1 Neat cement 2 Cement grout 3 Bentonite 4 Other Grout Intervals From 6 ft. to 6	A 44
Grout Intervals From 0 ft. to 20 ft. From ft. to ft.	ft. to ft.
Frout intervals From U ft. to 20 ft. From ft. to ft	
The state of the s	From ft. to ft.
viat is the hearest source of possible contamination:	14 Abandoned water well
1 Septic tank 4 Lateral lines 7 Pit privy 11 Fuel storage	
2 Sewer lines 5 Cess pool 8 Sewage lagoon 12 Fertilizer storage	je 16 Other (specify below)
3 Watertight sewer lines 6 Seepage pit 9 Feedyard 13 Insecticide stor	
Pirection from well? How many feet?	
FROM TO CODE LITHOLOGIC LOG FROM TO	PLUGGING INTERVALS
0 2 Surface Clay le	
2 10 Loess 179 180 Sandy	
	w/sandstrk
100 100 100 100 100 100 100 100 100 100	med sand
	some med sand w/sandy clay
	Some med sand w/sandy clay
	ind w/some med
125 142 Fine to med sand w/sandy clay 247 250 Clay	
	some med sand
142 147 Clay 259 263 Caliche	
147 170 Caliche w/clay strks 263 267 Sandy	
	e clay ued to pg 2
	e clay ued to pg 2
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, (3)	clay ued to pg 2 or (3) plugged under my jurisdiction and was
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, (2) reconstructed, (3) constructed, (4) reconstructed, (4) reconstructed, (5) reconstructed, (6) reconstructed, (7) reconstructed, (8) reconstructed, (9) reconstructed, (1) reconstructed, (1) reconstructed, (1) reconstructed, (2) reconstructed, (3) reconstructed, (4) reconstructed, (6) reconstructed, (1) reconstructed, (1) reconstructed, (2) reconstructed, (3) reconstructed, (4) reconstructed, (6) reconstructed, (6) reconstructed, (6) reconstructed, (7) reconstructed, (8) reconstructed, (8) reconstructed, (8) reconstructed, (9) reconstructed, (1) reconst	clay ued to pg 2 or (3) plugged under my jurisdiction and was best of my knowledge and belief. Kansas
CONTRACTOR'S OR LANDOWNER'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, (3) constructed, (4) reconstructed, (5) constructed, (6) constructed, (7) constructed, (8) constructed, (9) reconstructed, (9) constructed, (1) constructed, (1) constructed, (2) reconstructed, (3) constructed, (2) reconstructed, (3) constructed, (4) reconstructed, (6) constructed, (7) constructed, (8) constructed, (9) reconstructed, (9) reconstructed, (1) constructed, (1) constructed, (1) constructed, (1) constructed, (1) constructed, (2) reconstructed, (3) constructed, (4) reconstructed, (1) constructed, (2) reconstructed, (3) constructed, (4) co	clay ued to pg 2 or (3) plugged under my jurisdiction and was best of my knowledge and belief. Kansas

	WATER WELL RECORD Form	WWC-5 KSA 82a-1212 ID No. Sheet 2 of 2
LOCATION OF WATER WELL:	Fraction	Section Number Township Number Range Number
county: Seward	S 1/2 S 1/2 NW	11 T 31 S R 31 EW
istance and direction from nearest tow	on or city street address of well if located within	n city?
WATER WELL OWNER: Phyllis	Krauco	
RR#, St. Address, Box # : 105 W		Donat of Australian District of Mater Description
		Board of Agriculture, Division of Water Resources
City, State, ZIP Code : Plains	, NS 07009	Application Number: 20050113
AN "X" IN SECTION BOX:	4 DEPTH OF COMPLETED WELL	335 ft. ELEVATION:
N N	Denth/s) Groundwater Encountered 1	ft. 2 ft. 3 ft.
A	WELL'S STATIC WATER LEVEL 1	ft. below land surface measured on mo/day/yr
NWNE		ft. after hours pumping gpm
½ w X E	Est. Yield gpm: Well water wa	ts ft. after hours pumping gpm 340 ft. and in. to ft. c water supply 8 Air conditioning 11 Injection well eld water supply 9 Dewatering 12 Other (Specify below)
	Bore Hole Diameter 8 in. to	340 ft. and in. to ft.
	WELL WATER TO BE USED AS: Publi	c water supply 8 Air conditioning 11 Injection well
sw se	1 Domestic 3 Feed lot 6/Oil fie	eld water supply 9 Dewatering 12 Other (Specify below)
.		and garden (domestic) 10 Monitoring well
S	Was a chemical/bacteriological sample sub-	mitted to Department? Yes No X If yes, mo/day/yr sample was
	submitted	Water Well Disinfected? Yes X No
5 TYPE OF BLANK CASING USED:	5 Wrought Iron	8 Concrete tile CASING JOINTS: Glued Clamped
1 Steel 3 RMP ((SR) 6 Asbestos-Cement	9 Other (specify below) Welded
2 PVC 4 ABS	7 Fiberglass	Threaded
	in to ft Dia	in. to ft., Dia in. to ft.
		lbs./ft. Wall thickness or gauge No.
TYPE OF SCREEN OR PERFORATION	N MATERIAL	7 PVC 10 Asbestos-cement
1 Steel 3 Stainle	ess steel 5 Fiberalass	8 RMP (SR) 11 Other (specify)
2 Brass 4 Galvai	nized steel 6 Concrete tile	9 ABS 12 None used (open hole)
SCREEN OR PERFORATION OPENIN	NGS ARE: 5 Gauzed	9 ABS 12 None used (open hole) wrapped 8 Saw cut 11 None (open hole)
	Mill slot 6 Wire wra	pped 9 Drilled holes
2 Louvered shutter 4	Key punched 7 Torch cu	t 10 Other (specify)
SCREEN-PERFORATED INTERVALS:	: From ft. to	ft. From ft. to ft.
		ft. From ft. to ft.
GRAVEL PACK INTERVALS:		ft. From ft. to ft.
		ft. From ft. to ft.
6 GPOLIT MATERIAL 1 Next	coment 2 Coment grout	3 Bentonite 4 Other
Grout Intervals From	A to A Comment	5 Delitorate 4 Other
What is the nearest source of possible	nt. to nt. From	ft. toft. Fromft. toft.
-		10 Livestock pens 14 Abandoned water well
1 Septic tank	4 Lateral lines 7 Pit privy	11 Fuel storage 15 Oil well/ Gas well
		joon 12 Fertilizer storage 16 Other (specify below)
3 Watertight sewer lines	6 Seepage pit 9 Feedyard	13 Insecticide storage
Direction from well? FROM TO CODE	LITHOLOGIC LOG	How many feet? FROM TO PLUGGING INTERVALS
	ne to some med sand	PLOGGING INTERVALS
	andy clay	
	ne to some med sand	
	andy clay	
	ne to med sand	
	aliche & clay	
	ne sand w/caliche strk	
	ne to some med sand	
	R'S CERTIFICATION: This water well was (1) constructed, (2) reconstructed, or (3) plugged under my jurisdiction and was
7 CONTRACTOR'S OR LANDOWNE	TO OLIVINION TOTAL TING HOLD WOR WAS (
completed on (mo/day/yr)	4-29-05	and this record is true to the best of my knowledge and belief. Kansas
completed on (mo/day/yr)	4-29-05	This Water Well Record was completed on (mo/day/yr) 5-13-05
completed on (mo/day/yr) Water Well Contractor's License No.	4-29-05 554 Wooffer Pump & Well Inc	This Water Well Record was completed on (mo/day/yr) 5-13-05