


USE TYPEWRITER OR BALL
POINT PEN-PRESS FIRMLY,
PRINT CLEARLY.

WATER WELL RECORD
KSA 82a-1201-1215

Kansas Department of Health and
Environment-Division of Environment
(Water well Contractors)
Topeka, Kansas 66620

1. Location of well:		Fraction	Section number	Township number	Range number
Elliott #1, County Seward		1/4-SW 1/4 NE 1/4	25	T 31 S R 31 E/W	
2. Distance and direction from nearest town or city: to Hiway 160 - 4 mi. E - 4 mi. N - 1/2 mi. E South into location. Street address of well location if in city:		3. Owner of well: Sage Drilling Company R.R. or street: 500 Bitting Bldg. City, state, zip code: Wichita, Kansas 67202			
4. Locate with "X" in section below: 		6. Bore hole dia. 9 in. Completion date 6/18 Well depth 300 ft.			
5. Type and color of material		From	To	7. Cable tool <input checked="" type="checkbox"/> Rotary <input type="checkbox"/> Driven <input type="checkbox"/> Dug <input type="checkbox"/> Hollow rod <input type="checkbox"/> Jetted <input type="checkbox"/> Bored <input type="checkbox"/> Reverse rotary	
Surface		0	2	8. Use: <input type="checkbox"/> Domestic <input type="checkbox"/> Public supply <input checked="" type="checkbox"/> Industry <input type="checkbox"/> Irrigation <input type="checkbox"/> Air conditioning <input type="checkbox"/> Stock <input type="checkbox"/> Lawn <input checked="" type="checkbox"/> Oil field water <input type="checkbox"/> Other	
Clay		2	80	9. Casing: Material <input type="checkbox"/> Height: Above or below Threaded <input type="checkbox"/> Welded <input type="checkbox"/> Surface 28 in. RMP <input type="checkbox"/> PVC <input checked="" type="checkbox"/> Weight 2.78 lbs./ft. Dia. 5 in. to 295 ft. depth Wall Thickness: inches or Dia. 5 in. to 300 ft. depth gage No. 265	
Medium to lge. sand		80	140	10. Screen: Manufacturer's name Sawed Per. Type PVC Dia. 5 in. Slot/gauze .030 Length 60 in. Set between 235 ft. and 295 ft. Gravel pack? yes Size range of material 1/8-3/16	
Clay & med. to lge. sand 30-70		140	240	11. Static water level: 175 ft. below land surface Date 6/18/76	
Clay & med. to lge. sand 10-90		240	300	12. Pumping level below land surfaces: ft. after hrs. pumping g.p.m. ft. after hrs. pumping g.p.m. Estimated maximum yield 50 g.p.m.	
				13. Water sample submitted: mo./day/yr. Yes <input checked="" type="checkbox"/> No <input type="checkbox"/> Date	
				14. Well head completion: Pitless adapter 28 inches above grade	
				15. Well grouted? yes With: <input checked="" type="checkbox"/> Neat cement <input type="checkbox"/> Bentonite <input type="checkbox"/> Concrete Depth: From 0 ft. to 10 ft.	
				16. Nearest source of possible contamination: ft. 100 Direction NE Type Oilwell Well disinfected upon completion? <input checked="" type="checkbox"/> Yes <input type="checkbox"/> No	
				17. Pump: <input checked="" type="checkbox"/> Not installed Manufacturer's name Model number HP Volts Length of drop pipe ft. capacity g.p.m. Type: <input type="checkbox"/> Submersible <input type="checkbox"/> Turbine <input type="checkbox"/> Jet <input type="checkbox"/> Reciprocating <input type="checkbox"/> Centrifugal <input type="checkbox"/> Other	
18. Elevation:		19. Remarks:			
Topography: <input type="checkbox"/> Hill <input type="checkbox"/> Slope <input checked="" type="checkbox"/> Upland <input type="checkbox"/> Valley		(Use a second sheet if needed)			
		20. Water well contractor's certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Carlile Water Well Service, LLC Business name License No. Address Box 275, Liberal, Ks. Signed Edward E. Means Date 6/30 Authorized representative			

Forward the white, blue and pink copies to the Department of Health and Environment

Form WWC-5