## WATER WELL RECORD KSA 82a-1201-1215

Kansas Department of Health and Environment-Division of Environment (Water well Contractors) Topeka, Kansas 66620

	County Fraction			Section number		Township number Range number		
1. Location of well:	County							
	Seward	NE 1/4 NE 1/4 NW			32	T 31 s		<b>E</b>
2. Distance and direction from nearest town or city: 8 Miles W and 8. Owne R.R. or s				er of well: Mrs. Keith Rosson				
Street address of well location If in city:				ate, zip code: Plains, Kansas				
4. Locate with "X" in section below: Sketch map:					6. Bore hole dia. 28 in. Completion date 3-13-76			
N						Well depth 418 ft.		
430' W and 1650' N of t corner of the NW4, Sec.				The state of the s		7 Cable tool Rotary Driven Dug		
R31W, Seward County, Kans						8. Use: Domestic Public supply Industry X Irrigation Air conditioning Stock Lawn Oil field water Other		
						9. Casing: Material <u>STL</u> Height: Above or below Threaded Welded X Surface 12 in.		
						Threaded Welded Surface 12 in.  RMP PVC Weight 37 lbs./ft.		
1 Mile ——→1						Dia. 16in. to 184t. dep	th Wall Thickness: inc	hes or
5. Type and color of material				From	То	Diain. toft. depth gage No219		
						10. Screen: Manufacturer's n	ame Brown an	
Top soil				0	3	Type Louver Dia. 16"  Slot/gauze 1/8" Length 234'  Set between 184 ft. and 418 ft.		
Tan clay				3	46			
				46	66	ft. andft.		
Fine to coarse sand				1-0	"	Gravel pack? Yes Size range of material 3.4mm		
Tan clay				66	86	11. Static water level: mo./day/yr		
Fine to coarse sand clay streaks				86	150	12. Pumping level below land surfaces: 194 ft. after 1 hrs. pumping 1040 g.p.m.		
						194 ft. after 1   1 210 ft. after 1   1	ors, pumping 1040	g.p.m.
Blue Clay				150	178	Estimated maximum yield 3000 g.p.m.		
Fine to coarse sand				178	216	13. Water sample submitted: Yes X No	mo. Date	/day/yr.
Tan clay				216	226	14. Well head completion:		
				226	336	Pitless adapter	X Inches above	grade
Fine to coarse sand some small clay streaks						15. Well grouted? Yes	Rontonito	oncrete
Gray Clay				336	344	With: Neat cement _X Bentonite Concrete Depth: From ft. to 10_ ft.		
Fine to coarse sand some small clay streaks				344	418	16. Nearest source of possible contamination: Unk		
Timestone and alone				418	140	ft Direction Type Well disinfected upon completion? X Yes No		
Limestone and clay				410	440	17. Pump:	Not installed	
						Manufacturer's nameLayn  Model number 14TL	e & Bowler _ HP ∨ol	
						Length of drop pipe 280	ft. capacity 200	
						Туре:	X Turbine	
				<del> </del>		Submersible Jet	Recipro	
	(Use a second s	heet if needed)			L	Centrifugal	Other	8
18. Elevation:	19. Remarks:					20. Water well contractor's o		"
						This well was drilled under my is true to the best of my know		report
Topography:					Layne Wes		Co. Inc.	_150 ≨
Hill Slope					Business name  Address Garden City, Kansas			ense No.
X Upland						Signe	int Date	
Valley						Authorized rep	resentative 10 mg	<del>y 76</del> ∑
		en til te i					Form WW	